View NSN Online: https://aerobasegroup.com/nsn/6830-00-291-5008

Product ID:OXYGEN MSDS Date:09/01/1985 FSC:6830 NIIN:00-291-5008 **MSDS Number: BHDJS** === Responsible Party === **Company Name: UNION CARBIDE CORPORATION** Address:39 OLD RIDGEBURY ROAD Box:NA City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num: ROUTINE INFO CONTACT LOCAL SUPPLIER **Emergency Phone Num:1-8** 00-822-4357 CANADA 514-640-6400 CAGE:36346 === Contractor Identification === Company Name: HAMPTON ROADS SUPPLY UNION CARBIDE LINDE DIVISION Address:3450 VIRGINIA BEACH BLVD Box:12567 City:NORFOLK State:VA ZIP:23502-3123 Country:US CAGE:7D711 Company Name: UNION CARBIDE CORP LINDE DIV Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06817-0001 Country:US Phone:800-822-4357; 304-744-3487 CAGE:36346

Ingred Name:OXYGEN

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: BREATHING OXYGEN UNDER PRESSURE MAY CAUSE PROLONGATION OF ADAPTATION TO DARKNESSAND REDUCED PERIPHERAL VISION. Effects of Overexposure:SYMPTOMS INCLUDE NASAL STUFFINESS, COUGH, SORE THROAT, CHEST PAIN AND BREATHING DIFFICUL TY. BREATHING PURE OXYGEN UNDER PRESSURE MAY CAUSE LUNG DAMAGE AND ALSO CENTRAL NERVOUS SYSTEM EFFECTS RESULTING IN DIZZINESS, POOR COORDINATION, TINGLINSENSATION, VISUAL & HEARING DISTURBANCE, MUSCULAR TWITCHING, UNCONSCIOUSNESS, CONVUL First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NOT BREATHING. KEEP VICTIM WARM ANDAT REST. CALL A PHYSICIAN. Extinguishing Media: VIGOROUSLY ACCELERATES COMBUSTION. USE MEDIA APPROPRIATE FORSURROUNDING FIRE. WATER IS PREFERRED FOR CLOTHES FIRE. Fire Fighting Procedures: EVACUATE ALL PERSONNEL FROM DANGER AREA. IMMEDIATELY COOL CONAINERS WITH WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL, THEN MOVE CONTAINERS FROM FIRE AREA. Unusual Fire/Explosion Hazard:OXIDIZING AGENT, VIGOROUSLY ACCELERATES

COMBUSTION. CONTACT WITH FLAMMABLE MATERIALS MAY CAUSE FIRE OR EXPLOSION

CONTAINER MAY RUPTURE DUE TO HEAT OF FIRE.

Spill Release Procedures:SHUT OFF LEAK IF W/O RISK. VENTIALTE AREA OF LEAK OR MOVE LEAKING CONTAINER TO WELL-VENTILATED AREA.REMOVE ALL FLAMMABLE MATERIALS FROM VICINITY. OXY MUST NEVER BE PERMITTED TO STRIKE AN OILY SURFACE, GREASY CLOTHES, OR OTHER COMBUSTIBLE MATERIAL.

Handling and Storage Precau

tions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYS.BY VENTING TO A SAFE PLACE, THEN REPAIR THE LEAK. Other Precautions:NEVER LUBRICATE OXYGEN VALVES, REGULATORS, ETC., WITH ANY COMBUSTIBLE SUBSTANCE.USE A CHECK VALVE OR OTHER PROTECTIVE APPARATUS IN ANY LINE OF PIPING FROM THE CYLINDER TO PREVENT REVERSE FLOW.

======= Exposure Controls/Personal Protection ==========

Protective Gloves:PREFERRED FOR CYLINDER H ANDLING Eye Protection:SELECT IN ACCORDANCE W/OSHA29CFR1910.133 Other Protective Equipment:METATARSAL SHOES FOR CYLINDER HANDLING. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:-183C/-297F Vapor Pres:GAS Vapor Density:1.105 @25C Spec Gravity:GAS Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS, ODORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES COMBUSTIBLE MATERIALS, ASPHALT, FLAMMABLE MATERIALS, ESPECIALLY OILS AND GREASES.

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE, IN AN OPEN, OUTDOORS AREA. REMOVE ALL FLAMMABLE MATERIALS FROMVACINITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by e

## lements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.