

NATIONAL WELDERS SUPPLY CO INC -- ACETYLENE -- 6830-00-292-0137

=====
Product Identification
=====

Product ID:ACETYLENE

MSDS Date:07/01/1994

FSC:6830

NIIN:00-292-0137

MSDS Number: BHDKB

=== Responsible Party ===

Company Name:NATIONAL WELDERS SUPPLY CO INC

Address:810 GESCO

Box:31007

City:CHARLOTTE

State:NC

ZIP:28231

Country:US

Info Phone Num:704-333-5475

Emergency Phone Num:704-333-5475

CAGE:1826

4

=== Contractor Identification ===

Company Name:NATIONAL WELDERS SUPPLY CO INC

Address:810 GESCO ST

Box:31007

City:CHARLOTTE

State:NC

ZIP:28231

Country:US

Phone:704-333-5475

CAGE:18264

Company Name:NATIONAL WELDERS SUPPLY CO, INC

Address:2330 BOWDENS FERRY ROAD

Box:City:NORFOLK

State:VA

ZIP:23508

Country:US

Phone:804-627-5673

CAGE:0SSR7

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETYLENE

CAS:74-86-2

RTECS #:AO9600000

Other REC Limits:NONE GIVEN

ACGIH TLV

:ASPHYXIANT; 9495

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: ACETYLENE IS DEFINED AS A
SIMPLE ASPHYXIANT. OXYGEN LEVELS SHOULD BE MAINTAINED AT GREATER
THAN 18 MOLAR PERCENT AT NORMAL ATMOSPHERIC PRESSURE. CHRONIC:
REPEATED EXPSOURES HAVE NOT SHOWN DELET ERIOUS EFFECTS.

Explanation of Carcinogenicity:NOT CONSID
ERED TO BE A CARCINOGEN BY
NTP, IARC, OR OSHA.

Effects of Overexposure:INHALATION:SYMPTOMS SIMILAR TO THAT OF BEING
INTOXICATED. AT HIGHER CONCENTRATIONS, MAY EXCLUDE AN ADEQUATE
SUPPLY OF OXYGEN TO THE LUNGS CAUSING UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:PERSONS IN ILL HEALTH WHERE SUCH
ILLNESS WOULD BE AGGRAVATED BY EXPOSURE TO ACETYLENE SHOULD NOT BE
ALLOWED TO WORK WITH OR HANDLE THIS PRODUCT.

=====
===== First Aid Measures =====

====

First Aid:PROMPT MEDICAL ATTENTION IS MANDANTORY IN ALL CASES OF
OVEREXPOSURE TO ACETYLENE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH
SELF-CONTAINED BREATHING APPARATUS AND BE COGNIZANT OF EXTREME FIRE
AND EXPLO SION HAZARD.

=====
===== Fire Fighting Measures =====

Flash Point:GAS

Autoignition Temp:Autoignition Temp Text:565F

Lower Limits:2.2

Upper Limits:80 - 85

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:IF POSSIBLE,
STOP FLOW OF ESCAPING GAS. USE

WATER SPRAY TO COOL SURROUNDING CONTAINERS. KEEP PERSONNEL FROM
AREA SINCE HEATED CYLINDERS MAY RUPTURE VIOLENTLY.

Unusual Fire/Explosion Hazard:GASEOUS ACETYLENE IS SPONTANEOUSLY
COMBUSTIBLE IN AIR AT PRESSURES ABOVE 30 PSIA. IT REQUIRES A VERY
LOW IGNITION ENERGY SO THAT FIRES CAN REIGNITE VIOLENTLY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE
AP

PROPRIATE PROTECTIVE EQUIPMENT. IF LEAK IS IN USER'S EQUIPMENT,
BE CERTAIN TO PURGE PIPING WITH AN INERT GAS PRIOR TO ATTEMPTING
REPAIRS. IF LEAK IS IN CONTAINER OR VALVE, CONTACT SUPPLIER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY IN WELL-VENTILATED AREAS. DO
NOT DRAG, SLIDE OR ROLL CYLINDERS. USE A HAND TRUCK TO MOVE
CYLINDERS.DO NOT USE HEAT TO INCREASE DIS
CHARGE RATE

Other Precautions:VALVE PROTECTION CAPS MUST REMAIN IN PLACE UNLESS
CONTAINER IS SECURED WITH VALVE OUTLET PIPED TO USE POINT. DO NOT
ALLOW THE FREE GAS TO EXCEED 30 PSIA (207 KPA). EARTH-GROUND AND
BOND ALL LINES AND EQUIPMENT ASSOCIATED WITH THE SYSTEM.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:POSITIVE PRESSURE AIR LINE OR SELF-CONTAINED
BREATHING APPARATUS SHOULD BE AVAILABLE FOR EMERGENCY USE.

Ventilation:HOOD WITH

TH FORCED VENTILATION. MECHANICAL EXHAUST IN
ACCORDANCE WITH ELECTRICAL CODES.

Protective Gloves:PVC OR RUBBER

Eye Protection:SAFETY GOGGLES OR GLASSES.

Other Protective Equipment:SAFETY SHOES, SAFETY SHOWER.

Work Hygienic Practices:USE GOOD HYGIENE PRACTICES.

Supplemental Safety and Health

STORE IN A COOL, DRY, WELL-VENTILATED PLACE AWAY FROM INCOMPATIBLE
MATERIALS. SINCE ACETYLENE WILL EXPLODE OR COMBUST IF ITS PRESSURE
EXCEEDS 30 PSIA, IT IS SHIPPED DISSOLVED IN ACETONE OR DIMETHY
L FOR

MAMIDE WHICH IS DISPERSED IN A POROUS MASS WITHIN THE CYLINDER.

=====
===== Physical/Chemical Properties =====

HCC:G2

Boiling Pt:B.P. Text:-119F,-84C

Melt/Freeze Pt:M.P/F.P Text:-113F,-81C

Vapor Pres:33359

Vapor Density:1.107KG/M3

Spec Gravity:0.906

Evaporation Rate & Reference:N/A, DISSOLVED GAS

Solubility in Water:APPRECIABLE

Appearance and Odor:A COLORLESS GAS WITH A DISTINCTIVE GARLIC-LIKE
ODOR.

=====
===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:NO

OXYGEN AND OTHER OXIDIZERS INCLUDING ALL OF THE HALOGENS AND HALOGEN COMPOUNDS, COPPER, MERCURY, SILVER, BRASS.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES. DO NOT ALLOW THE FREE GAS TO EXCEED 30 PSIA. AVOID SUDDEN SHOCK OR HEAT.

Hazardous Decomposition Products:CARBON AND HYDROGEN.

Conditions to Avoid Polymerization:DO NOT ALLOW FREE GAS TO EXCEED 30 PSIA. CYLINDERS SHOULD NOT BE EXPOSED TO SUDDEN SHOCK OR SOURCES OF HEAT.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF WASTE OR UNUSED QUANTITIES. RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE TO YOUR SUPPLIER. FOR EMERGENCIES, CONTACT SUPPLIER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.