

PACKAGING SERVICE CO., INC. -- TT-T-291 TYPE 1 -- 8010-00-558-7026

=====
Product Identification
=====

Product ID:TT-T-291 TYPE 1

MSDS Date:01/01/1987

FSC:8010

NIIN:00-558-7026

MSDS Number: BHDNF

=== Responsible Party ===

Company Name:PACKAGING SERVICE CO., INC.

Address:4704 SHANK ROAD

Box:875

City:PEARLAND

State:TX

ZIP:77581

Country:US

Info Phone Num:(713) 485-1457

Emergency Phone Num:(713) 485-1
457

Preparer's Name:SCIENTIFIC INFO SERVICES

CAGE:9V846

=== Contractor Identification ===

Company Name:PACKAGING SERVICES INC

Address:472 SHANK RD

Box:875

City:PEARLAND

State:TX

ZIP:77581

Country:US

Phone:713-485-1457

CAGE:9V846

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS (VP 2 MM HG @ 20 DEG. C)

CAS:64475-85-0

RTECS #:PY8240000

OSHA PEL:500 PPM 2950 MG/CU.M

ACGIH TLV:100 PPM 525 MG/CU.M.

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:YES
Health Hazards Acute and Chronic:ACUTE: INHALATION OF VAPORS MAY BE
NARCOTIC OR ANESTHETIC.INGESTION OR LIQUID WILL CAUSE
GASTROINTESTINAL DISTRESS,IRRITATION,&POSSIBLY NAUSEA.LIQUID OR
VAPORS MAY BE IRRITATING TO SKIN AND EYES. C HRONIC: KIDNEY &
LIVER DAMAGE POSSIBLE.
Effects of Overexposure:SIGNS OF INHALATION OVEREXPOSURE,IN ORDER
IRRITATION O
F RESPIRATORY TRACT, NERVOUSE SYSTEM
DEPRESSION.HEADACHES,DIZZINESS,STAGGERING
GAIT,CONFUSION,UNCONSCIOUSNESS,COMA.
Medical Cond Aggravated by Exposure:BREATHING DISORDERS, DERMATITIS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR AND IF NEEDED
ARTIFICIAL RESPIRATION.GIVE OXYGEN IF BREATHING IS LABORED.GET
EMERGENCY MEDICAL HELP.CONTACT PHYSICIAN IMMEDIATELY. INGESTION:
DO NOT INDUCE VOMITING, GET
IMMEDIATE MEDICAL ATTN.FLUSH EYES &
SKIN WITH WATER.GET MEDICAL ATTN IF SYMPTOMS DEVELOP & PERSIST.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:111F
Lower Limits:7%
Upper Limits:1%
Extinguishing Media:WATER FOG OR SPRAY,FOAM,DRY POWDER,CARBON DIOXIDE
CO2.
Fire Fighting Procedures:APPROACH FIRE FROM UPWIND SIDE.AVOID BREATHING
SMOKE,FUMES,MIST,OR VAPORS ON THEDOWNWIND SIDE.
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPT
URE FROM INTERNAL
PRESSURE IF CONFINED TO FIRE AREA.COOL W/WTR. GET NONESSENTIAL
PEOPLE OUT OF THE AREA.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILLS,PICK UP W/ABSORBENT MEDIA.STORE
AS HAZARDOUS WASTE.LARGE SPILLS,CONTAIN W/DIKES,PICK UPW/VACCUM
TRUCK.HANDLE AS HAZARDOUS WASTE.NOTIFY PROPER LOCAL,STATE &
FEDERAL AGENCIES.FOR VAPOR RE LEASE,GET PERSONNEL OUT OF AREA.SHUT
OFIGNI SOURC

===== H

Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL PLACE AWAY FROM
IGNITION SOURCES.

Other Precautions:STORE AWAY FROM OXIDIZERS OR MATERIALS BEARING A
YELLOW "DOT" LABEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED ORGANIC VAPOR MASK.

Ventilation:LOCAL/MECHANICAL DESIRED

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:CHEMICAL GOGGLES/FULL FACE SHIELD.

Other Protective E

quipment:NOT NORMALLY NEEDED.

Work Hygienic Practices:AVOID CONTACT W/SKIN,EYES & CLOTHING.AFTER

HANDLING THIS PRODUCT,WASH HANDS.IF CONTACT OCCURS,REMOVE CLOTHING.

Supplemental Safety and Health

WORK HYGIENE: IF NEEDED,TAKE FIRST AID ACTION.LAUNDER CONTAMINATED
CLOTHING BEFORE REUSE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323F

Melt/Freeze Pt:M.P/F.P Text:NO

Vapor Pres: