View NSN Online: https://aerobasegroup.com/nsn/6830-00-564-8989

Product ID:ARGON MSDS Date:10/01/1985 FSC:6830 NIIN:00-564-8989 MSDS Number: BHDNK === Responsible Party === Company Name: LIQUID AIR CORPORATION Address:2121 N. CALIFORNIA BLVD. City:WALNUT CREEK State:CA ZIP:94596 Country:US Info Phone Num:415-977-6500 Emergency Phone Num:414-977-6500 CAGE:DO426 === Contractor Identification === Company Name: LIQUID AIR CORP ONE CALIFORNIA PLAZA Address:2121 N. CALIFORNIA BLVD Box:City:WALNUT CREEK State:CA ZIP:94596 Country:US Phone:415-977-6500 CAGE:18260 Company Name: LIQUID AIR CORPORATION Address:2121 N. CALIFORNIA BLVD., SUITE 350 City:WALNUT CREEK State:CA ZIP:94596 Phone:510-977-6500 CAGE:DO426 Company Name: WELCO GASES CORP. CAGE:0C525

Ingred Name:ARGON CAS:7440-37-1

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ARGON IS NONTOXIC BUT THE LIBERATION
OF A LARGE AMOUNT IN A CONFINED AREA COULD DISPLACE THE AMOUNT OF
OXYGEN IN AIR NECESSARY TO SUPPORT LIFE.
Effects of Overexposure:MAY INCLUDE ANY,ALL,OR NONE OF THE
FOLLOWING:DIZZINESS,TIGHTNESS OF FOREHEAD,TINGLING
TONGUE,FINGERTIPS OR TOES,WEAKENED SPE
ECH LEADING TO INABILITY TO
UTTER SOUNDS,RAPID REDUCTION IN ABILITY TO PERFO RM
MOVEMENTS,REDUCED CONSCIOUSNESS OF SURROUNDINGS,LOSS OF TACTILE
SENSATIONS,&HEIGHTED MENTAL ACTIVITY.

First Aid:PROMPT MEDICAL ATTN IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO ARGON.RESCUE PERSONNEL SHOULD BE EQUIPPED W/SELF-CONTAINED BREATHING APPARATUS.CONSCIOUS/UNCONSCIOUS PERSONS SHOULD BE MOVED TO UNCONTA MINATED AREA

.UNCONSCIOUS PERSON SHOULD BE GIVEN MOUT-TO-MOUTH RESUSCITATION & SUPPLEMENTAL OXYGEN.QUICK REMOVAL FROM THE CONTAMINATED AREA IS MOST IMPORTANT.

Extinguishing Media:NONFLAMMABLE, INERT GAS

Spill Release Procedures: EVACUATE ALL PERSONNEL FROM AREA. USE APPROPRIATE PROTECTIVE EQUIP.IF LEAK IS IN CONTAINER OR CONTNRVALVE, CONTACT YOUR CLOSEST S UPPLIER LOCATION OR CALL THE EMERGENCY TELEPHONE NUMBER LISTED HEREIN.

 Handling and Storage Precautions:USE IN WELL-VENTILATED AREAS.DO NOT DRAG,SLIDE, ORROLL CYLS.USE SUITABLE HAND TRUCK. PROTECT CYLNDRSFROM PHYSICAL DAMAGE. SEGREGATE FULL/EMPTY CYLNDRS
 Other Precautions:COMPRESSED GAS CYLS SHOULD NOT BE FILLED EXCEPT BY QUALIFIED PRODUCERS OF COMPRESSED GAS.SHIPMENT OF COMPRESSED GAS CYL WHICH HAS NOT B EEN FILLED BY THE OWNER OR W/HIS WRITTEN CONSENT IS A VIOLATION OF FEDERAL LAW (49CFR).

Respiratory Protection: POSITIVE PRESSURE AIR LINE W/MASK OR SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR EMERGENCY USE. Ventilation: TO PREVENT ACCUMULATION OF HIGH CONCENTRATIONS SO AS TO REDUCE THE OXYGEN LEVEL IN THE AIR TO LESS THAN 18 MOLAR %. Protective Gloves: ANY MATERIAL Eye Protection: SAFETY GOGGLES/GL ASSES Other Protective Equipment: SAFETY SHOES Supplemental Safety and Health NK

Boiling Pt:B.P. Text:-302.55F Vapor Pres:>-188.12F Vapor Density:.1034LBFT3 Spec Gravity:1.38@70F AIR=1 Solubility in Water:BUN COEF .0340 @ 68F Appearance and Odor:COLORLESS, ODORLESS GAS

Stability Indicator/Materials to Avoid:YES NONE Hazardous Decomposition Products:NONE

===

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF WTR OR UNUSED QTYS.RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED,W/VALVE OUTLET PLUGS OR CAPS SECURED & VALVE PROTEC-TION CAP IN PLACE TO YOUR SUPPLIER. FOR EMERGENCY DISPOSAL CALL CLOSEST SUPPLIER OR CALL EMER NO.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.