View NSN Online: https://aerobasegroup.com/nsn/8010-00-848-9272

ILLINOIS BRONZE PAINT -- AEROSOL SPRAY PAINT FLAT O.D. 34088 -- 8010-00-848-9272

======== Product Identification ============

Product ID:AEROSOL SPRAY PAINT FLAT O.D. 34088

MSDS Date:06/01/1984

FSC:8010

NIIN:00-848-9272

MSDS Number: BHDXD === Responsible Party ===

Company Name: ILLINOIS BRONZE PAINT

Address:300 E. MAIN STREET

Box:NA

City:LAKE ZURICH

State:IL ZIP:60047 Country:US

Info Phone Num:312-438-8201

Emergency Phone Num:312-359-6433

CAGE:91794

=== Contractor Identification ===

Company Name: ILLINOIS BRONZE PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

====== Composition/Information on Ingredients ========

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 25.1%

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (S

ARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: 0.5% OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB
Ingred Name:METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 29.3% OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 29.3% OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9192
Ingred Name:RESIN OSHA PEL:NA AC GIH TLV:NA
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Effects of Overexposure:INHALATION: ANESTHETIC IRRITATION OF THE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF THE
RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM. DEPRESSION
CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING
GAIT, CONFUSIONUNCONSCIOUSNESS OR COMA. SKIN/EYE: PRIM ARY
IRRITANT.

First Aid:INHAL:REMOVE TO FRESH AIR.

RESTORE BREATHING. CONSULT A PHYSICIAN. EYES: FLUSH IMMEDIATELY W/LARG AMOUNTS OF WTR FOR 15 MINS. TAKE TO A PHYSICIAN. SKIN: WIPE OFF WITH TOWEL. REMOVER REMAINDER WITH M INERAL SPIRITS, TURPENTINE, OR LACQUERTHINNER. WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. Flash Point:-40F/-40C Upper Limits:1.3 Extinguishing Media: FOAM, CO2, DRY CHEMICAL Unusual Fire/Explosion Hazard: CANS WILL RUPTURE FROM INTERNAL PRESSURE AT ABOUT 190F & DISCHARGE FLAMMABLE CONTENTS. WHEN HEADED TO DECOMPOSITON, TOXIC FUMES ARE FORMED. ======== Accidental Release Measures ============ Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION FLAMES, ELECTRICAL, HOT SURFACES, STATIC, OR FRICTIONAL SPARKS. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT. ============ Handling and Storage =========================== Handling and Storage Precautions :STORE LARGE QUANTITIES IN BLDG. DESIGNED & PROTECTFOR STORAGE OF NFPA CLASS 1A FLAMMABLE LIQUIDS. DO NOT STORE ABOVE 120F. Other Precautions: DO NOT SPRAY IN EYES. DO NOT PUNCTURE OR INCINERATE CANS. DO NOT STICK PIN OR ANY SHARP OBJECTS INTO OPENING ON TOP OF CAN. FINGER MUST NOT PROTRUDE OVER SPRAY BUTTON. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: FOR CASUAL USE NONE REQUIRED, PROVIDED VENTILATION IS AVAILABLE AS OUTL INED BELOW. Ventilation: GENERAL/LOCAL EXHAUST IN VOLUME & PATTERN TO KEEP TLV OF MOST HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS. Protective Gloves:NONE Eye Protection: NONE Other Protective Equipment:NONE Supplemental Safety and Health NK ========= Physical/Chemical Properties =========== HCC:V3 Boiling Pt:B.P. Text:104-232F Vapor Density:> AIR Evaporation Rate & Properties
Evaporation Rate & Properties Percent Volatiles by Volume:87.3

======== Stability and Reactiv

Stability Indicator/Materials to Avoid:YES NK Hazardous Decomposition Products:HYDROGEN CHLORIDE, CARBON MONOXIDE PHOSGENE
======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

ity Data =========