View NSN Online: https://aerobasegroup.com/nsn/8010-00-903-9177

THE SHERWIN WILLIAMS COMPANY -- (KEM *TRADE MARK) BULLETIN COLOR BLK C20B1

8010-00-903-9177

============ Product Identification =========================

Product ID:(KEM *TRADE MARK) BULLETIN COLOR BLK C20B1

MSDS Date:01/13/1983

FSC:8010

NIIN:00-903-9177

MSDS Number: BHDYF === Responsible Party ===

Company Name: THE SHERWIN WILLIAMS COMPANY

Address:101 PROSPECT AVENUE N.W.

City:CLEVELAND

State:OH ZIP:44115 Country:US

Inf

o Phone Num:(216) 566-2902

Emergency Phone Num: (216) 566-2917

CAGE:82927

=== Contractor Identification ===

Company Name: SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

Company Name: THE SHERWIN WILLIAMS COMPANY

Address:101 PROSPECT AVENUE N. W.

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:216-566-2917/216-566-2902

CAGE:82927

======= Composition/Information on Ingredients =

=========

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 2.0)

Fraction by Wt: 45% OSHA PEL:NKNE

ACGIH TLV:100 PPM/581 MG/M3

Ingred Name: LEAD DRIER (OSHA PEL FROM 29CFR 1910.1025)

Fraction by Wt: 0.04%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3 (PB);8990

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure: INHALATION: HIGH CONCENTRATION OF VAPORS ARE

ANESTHETIC.MAY CAUSE IRRI

TATION, LIGHTHEADEDNESS AND STAGGERING

GAIT. SKIN:MAY CAUSE

IRRITATION.

First Aid:EYES:FLUSH WITH COPIOUS QUANTITIES OF WATER FOR 15 MINUTES.

SKIN:WAS AFFECTED AREA WITH WATER.

INHALATION: REMOVE FROM EXPOSURE,

RESTORE BREATHING, KEEP WARM AND QUIET.SYMPTOMS MAY NOT BE

IMMEDIATELY APPARENT.OBTAIN MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:100F/37.78C

Upper Limits:1.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: USE S.C.B.A. WATER SPRAY MAY BE INEFFECTIVE.

IF USED FOG NOZZLES ARE PREFERABLE WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, & OPEN FLAME. APPLICATIONS TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

======= Accide

ntal Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.VENTILATE AND REMOVE WITH INERT ABSORBENT.
=========== Handling and Storage ============
Handling and Storage Precautions:CONTENTS ARE COMBSTBLE.KEEP AWAY FROM HEAT & OPEN FLAME.USE ONLY W/ADEQ VENTILATION.CLOSE CONTAINER WHEN NOT IN USE,DO NOT TRF CONTENTS TO OTH CONTNRS Other Precautions:DO NOT APPLY ON TOYS & OTH CHILDREN'S ARTICLES,OR ANY INTERIOR/EX TERIOR SURFACE WHICH MAY BE OCCUPIED OR USED BY CHILDREN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF ENGINEERING AND ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS ARE NOT FEASIBLE,USE RESPIRATORY DEVICES APPROVED BY NIOSH/MESA FOR PROTECTION AGAINST SPRAY MIST AND VAPORS. Ventilation:LOCAL EXHAUST PREFERABLE.MECHANICAL (GENERAL) EXHAUST ACCEPTABLE.SPEC VENT REQUIRED TO KEEP BELOW TLV AND LEL. Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT. Eye Protection:SAFETY SPECS.W/UNPERFORATED SIDESHIELDS Other Protective Equipment:CONSULT NFPA CODE,USE APPROVED BONDING AND GROUNDING PROCEDURES. Work Hygienic Practices:WASH HANDS AFTER USING. Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:300-395F Vapor Density:>AIR Evaporation Rate & Description Rate & Percent Volatiles by Volume:56.1
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES NK Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF LEAD
======= Disposal Considerations ==========
Waste Disposal Methods:INCINERATE IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINER.DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE,AND LOCAL REGULATIONS REGARDING POLLUTION.
Disclaimer (provided with this information by the compiling agencie

s):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.