Company Name:OCTAGON PROCESS INC. Address:596 RIVER ROAD City:EDGEWATER State:NJ ZIP:07020

ZIP:07020 Country:US

Info Phone Num:201-945-9400

E

mergency Phone Num:201-945-9400

CAGE:82925

=== Contractor Identification ===

Company Name: OCTAGON PROCESS INC.

Address:596 RIVER ROAD Box:City:EDGEWATER

State:NJ ZIP:07020 Country:US

Phone:201-945-9400

CAGE:82925

======= Composition/Information on Ingredients ========

Ingred Name:PETROLEUM DISTILLATE

CAS:65996-93-2 Fraction by Wt: 90% OSHA PEL:NA ACGIH TLV:NA

========= Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:YES Ingestion

:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATION TO SKIN, EYES, MUCOUS MEMBRANES. HIGH VAPOR CONCENTRATION CAN CAUSE CNS DEPRESSION. PROLONGED SKIN CONTACT CAN CAUSE DERMATITIS LIKE CONDITION Effects of Overexposure:EYES: TEARING & SLIGHT BURNING SENSTATION. SKIN: DEFATTING & REDNESS. INHALATION: HEADACHE, DIZZINESS,
WEAKNESS, LOSS OF COORDINATION.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE
======================================
irst Aid Measures ============
First Aid:SKIN: WASH AREA W/MILD SOAP & WATER. IF IRR PERSISTS, GET MED AID. EYES: FLUSH W/WATER FOR AT LEAST 15 MIN. IF IRRI PERSISTS, GET MED AID. INHALATION: REMOVE TOFRESH AIR. TREAT SYMPTOMATICALLY. IF ING ESTED: DO NOT INDUCE VOMITING - GET IMMEDIATE MEDICAL ATTENTION
======================================
Flash Point Method:TCC Flash Point:158 F 70 C Lower Limits:ND Upper Limits:ND Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures: USE PROPER PROTECTIVE EQUIPMENT IN ENCLOSED OR CONFINED AREAS. KEEP FIRE EXPOSEDCONTAINERS COOL WITH WATER SPRAY Unusual Fire/Explosion Hazard: NONE
========== Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE AREA TO CONTAIN. SML: SHOULD BE ABSORBED ON SUITABLE MEDIA & PLACED IN DISPOSAL CONTAINER. LRG: CAN BE VACUUMED &THEN PLACED IN DISPOSAL CONTAIN
ER. DO NOT ALLOW PR ODUCT TO ENTER WATERCOURSES.
========== Handling and Storage ===========
Handling and Storage Precautions:STORE IN COOL, DRY PLACE. KEEP AWAY FROM STRONG OXIDIZING MATERIALS. STORE AWAY FROM OPEN FLAMES, SPARKS, ETC. KEEP CONTAINER CLOSED WHEN NT IN USE Other Precautions:LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. DO NOT RE-USE CONTAINER
====== Exposure Controls/Personal Protection ========

Respiratory Protection:IN CONFI

NED AREAS, USE ORGANIC VAPOR RESPIRATOR Ventilation:LOCAL EXHAUST Protective Gloves: RUBBER NEOPRENE Eye Protection: CHEMICAL SAFETY GOGGLES & /OR FACE SHIELD Other Protective Equipment: AS NEEDED TO AVOID EYE AND SKIN CONTACT. EYE WASH FOUNTAIN. SAFETY SHOWER. Work Hygienic Practices: WASH HANDS & FACE AFTER USING & BEFORE EATING, DRINKING OR USING TOILET FACILITIES. Supplemental Safety and Health NK ======== Physical/Chemical Properties ============ HCC:V4 Boiling Pt:B.P . Text:456 F Melt/Freeze Pt:M.P/F.P Text:ND Vapor Pres:ND Vapor Density:ND Spec Gravity: 0.87 @ 77 F Evaporation Rate & Deference: ND Solubility in Water: NEGLIGIBLE Appearance and Odor: AMBER COLORED LIQUID, PETROLEUM-LIKE ODOR ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING MATERIALS Stability Condition to Avoid: OPEN FLAMES, SPARKS, HIGH ENERGY SOURCES Hazardous Decomposition Products: NONE KNOWN _____ === Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing

this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.