

RAYCHEM CORPORATION -- S-1030 ADHESIVE -- 8040-01-044-4976

=====
Product Identification
=====

Product ID:S-1030 ADHESIVE

MSDS Date:05/01/1988

FSC:8040

NIIN:01-044-4976

MSDS Number: BHFCV

=== Responsible Party ===

Company Name:RAYCHEM CORPORATION

Address:300 CONSTITUTION DRIVE

City:MENLO PARK

State:CA

ZIP:94025

Country:US

Info Phone Num:415-361-5524

Emergency Phone Num:415-361-5524

Preparer's Name

:ARLENE KLONOFF

CAGE:06099

=== Contractor Identification ===

Company Name:RAYCHEM CORP

Address:300 CONSTITUTION DRIVE

Box:City:MENLO PARK

State:CA

ZIP:94025-1164

Country:US

Phone:415-361-4907

CAGE:06090

Company Name:RAYCHEM CORPORATION

Address:300 CONSTITUTION DRIVE

City:MENLO PARK

State:CA

ZIP:94025

Phone:(415)361-3333

CAGE:06099

=====
Composition/Information on Ingredients
=====

Ingred Name:NO HAZARDOUS LISTED

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:DURING NORMAL CONDITIONS OF USE, THIS PRODUCT
POSES NO KNOWN ACUTE/CHRONIC HEALTH HAZARD BY ANY ROUTE OF
ENTRY.

===== First Aid Measures =====

First Aid:EYES: IF MOLTEN MATERIAL CONTACTS THE EYE, FLUSH WITH WATER
FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN: IF
MOLTEN MATERIAL CONTACTS THE SKIN, TREAT AS A BURN. COOL
IMMEDIATELY
IN WATER. DO NOT ATTEMPT TO REMOVE MATERIAL STUCK ONTO
THE SKIN. SEEK MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH
AIR. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point:NA
Extinguishing Media:CARBON DIOXIDE, WATER, DRY CHEMICAL, FOAM
Fire Fighting Procedures:TOXIC FUMES MAY BE EVOLVED IN A FIRE. FIREMEN
SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED
AREAS.

===== Handling and Storage =====

Other Precautions:INSTALLATION: SEE APPROPRIATE RAYCHEM INSTALLATION
GUIDE

===== Exposure Controls/Personal Protection =====

Ventilation:IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE PRACTICE, ENSURE
ADEQUATE VENTILATION DURING INSTALLATION.
Supplemental Safety and Health
PROTECTIVE CLOTHING AND EQUIPMENT: TO BE BASED ON THE OPERATION
PERFORMED, FOLLOWING OSHA, ANSI, AND NIOSH GUIDELINES.

===== Physical/Chemical Properties =====

=====

HCC:N1

Vapor Pres:NIL

Spec Gravity:1.0 +/- 0.05

pH:NA

Solubility in Water:NIL

Appearance and Odor:BLACK, THIN, RUBBERY TAPE. NO ODOR.

Percent Volatiles by Volume:NA

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NK

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE AND
LOW MOLECULAR WEIGHT HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:NORMAL METHODS BASED ON FEDERAL, STATE, AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their
particular situation.