

EVERSEAL MANUFACTURING CO., INC. -- WHITE SG ALKYD ENAMEL 27875 -- 8010-00-286-7839

=====  
Product Identification  
=====

Product ID:WHITE SG ALKYD ENAMEL 27875

MSDS Date:10/21/1987

FSC:8010

NIIN:00-286-7839

MSDS Number: BHFPG

=== Responsible Party ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

Address:475 BROAD AVENUE

City:RIDGFIELD

State:NJ

ZIP:07657

Country:US

Info Phone Num:201-943-4986

Emer

gency Phone Num:201-943-4986

CAGE:EO432

=== Contractor Identification ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

CAGE:EO432

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

=====  
Composition/Information on Ingredients  
=====

Ingred Name:RESIN

Fraction by Wt: 25%

Other REC Limits:NA

OSHA PEL:NA

ACGIH TLV:NA

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by

Wt: 20%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Fraction by Wt: 26%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:MINERAL SPIRITS  
(VAPOR PRESSURE 2)  
CAS:64742-88-3  
Fraction by Wt: 25%  
OSHA PEL:120 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO  
IARC:NO OSHA:NO  
Effects of Overexposure:INHALATION: DIZZINESS, NAUSEA, POSSIBLE  
UNCONSCIOUSNESS. IRRITATION TO SKIN AND EYES

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY CPR IF NECESSARY.  
SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER. CONSULT A  
PHYSICIAN

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:105 F/40.56 C  
Lower Limits:1.0  
Extinguis  
hing Media:FOAM, CO2, DRY CHEMICAL  
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTING MEDIUM.  
FIREFIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE ADEQUATE  
VENTILATION. ABSORB SMALL SPILLS ON DRY ABSORBTION MATERIALUSE  
SPARK PROOF SCOOP FOR LARGER SPILLS

=====  
Handling and Storage  
=====

Handling and Storage P

recautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION  
SOURCES.

Other Precautions:NPCA/HMIS RATING 3,2,0,H.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV MAY BE EXCEEDED, USE CARTRIDGE FUME MASK.

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM

Supplemental Safety and Health

NK

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323-390 F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:44

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NA

Hazardous Decomposition Products:CARBON MONOXIDE AND/OR CARBON DIOXIDE  
ON COMBUSTION

=====  
===== Disposal Considerations =====

Waste Dispos

al Methods:DISPOSE OF AS PER LOCAL AND FEDERAL REGULATIONS  
FOR HAZARDOUS WASTE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume

responsibility for the suitability of this information to their particular situation.