

GENERAL ELECTRIC CO. SILICONE PRODUCTS DIV -- RT V162 SEALANT -- 8040-00-938-1535
===== Product Identification =====

Product ID:RT V162 SEALANT

MSDS Date:03/06/1989

FSC:8040

NIIN:00-938-1535

MSDS Number: BHFTS

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO. SILICONE PRODUCTS DIV

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:(518) 237-3330 (24 HRS)

Emergency Phon

e Num:(518) 237-3330 (24 HRS)

Preparer's Name:DA POLSINELLI

CAGE:0D424

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO SILICONE PRODUCTS

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330

CAGE:0D424

===== Composition/Information on Ingredients =====

Ingred Name:METHYLTRIMETHOXYSILANE

CAS:1185-55-3

Fraction by Wt: 1-5%

OSHA PEL:200 (R)PPM

ACGIH TLV:200 (R)PPM

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION: MAY BE HARMFUL IF
SWALLOWED. SKIN: MAY OCCUR IN SENSITIVE INDIVIDUALS
INHALATION: CAUSES MILD RESPIRATORY IRRITATION. APPLIES ONLY IN UNCURED STATE.
EYE CONTACT: UNCURED PROD CONTACT IRRITATES. MEDICAL CONDITIONS
AGGRAVATED: NKOTHER: NONE KNOWN. CHRONIC EFFECTS OF OVEREXPOSURE:
NONE KNOWN

Explanation of Carcinogenicity:THIS PRODUCT OR ONE OF ITS INGREDIENTS
PRESENT 0.1% OR MORE NOT LISTED.

Medical Cond Aggravated by Exposure:SKIN IRRITATION MAY OCCUR IN
CERTAIN SENSITIVE INDIVIDUALS.

===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. GIVE WATER OR MILK. GET
MED ATTEN. SKIN: DRY WITH CLOTH OR PAPER TOWEL. WASH WITH SOAP AND
WATER. INHALATION: GET FRESH AIR. EYES: FLUSH WITH WATER 15 MIN.
GET MED A TTEN.

=====

===== Fire Fighting Measures =====

Flash Point:NA
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA
Fire Fighting Procedures:NONE KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT
MATERIAL.PLACE IN CONTAINER FOR DISPOSAL. WASH WALKING SURFACES
WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARDWEAR PROPER
PROTECTIVE EQUIPMENT AS SPECIFIED
IN THE PROTECTIVE EQUIPMENT SECTION.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES.USE
IN WELL VENTILATED AREA. REMOVE CONTACT LENSES BEFORE USING
SEALANT.RESIDUAL MAY REMAIN ON FINGERS FOR SEV DAYS.
Other Precautions:USE IN WELL VENTILATED AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE IN A WELL VENTILATED AREA.
Ventilation:USE ONLY IN A

WELL VENTILATED AREA.

Protective Gloves:CLOTH GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE KNOWN

Work Hygienic Practices:CLEAN SEALANT FROM FINGERTIPS, NAILS AND

CUTICLES. RESIDUE MAY TRANSFER TO LENSES AND CAUSE EYE IRRITATION.

Supplemental Safety and Health

EYEWASH STATIONS AND GOOD VENTILATION.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:NEG

Vapor Density:NEG

Spec Gravity

:1.085

pH:NA

Evaporation Rate & Reference: