View NSN Online: https://aerobasegroup.com/nsn/6830-00-785-3306

Product ID:RACON 114 MSDS Date:04/07/1989 FSC:6830 NIIN:00-785-3306 MSDS Number: BHGDX === Responsible Party === Company Name: RACON INC. Address:6040 SOUTH RIDGE ROAD Box:198 **City:WICHITA** State:KS ZIP:67201 Country:US Info Phone Num:316-524-3245 Emergency Phone Num:415-821-5338 (MEDICAL) CAGE:EO152 === Contractor Ident ification === Company Name: ELF ATOCHEM NORTH AMERICA (FORMERLY RACON INC) Address:6040 S RIDGE RD Box:198 City:WICHITA State:KS ZIP:67201 Country:US Phone:CALL COLLECT 415-821-5338 CAGE:2A580 Company Name: RACON INC. Address:6040 SOUTH RIDGE ROAD Box:198 City:WICHITA State:KS ZIP:67201 Country:US Phone:316-524-3245 CAGE:EO152 Ingred Name: DICHLOROTETRAFLUOROETHANE (SARA III) CAS:76-14-2 RTECS #:KI1101000 Fraction by Wt: 100% 0

SHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 Ozone Depleting Chemical:1

LD50 LC50 Mixture:LC50 >50000 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT. IT WILL DEFAT & DRY SKIN,POSSIBLY CAUSING DERMATITIS. VAPOR IS HEAVIER THAN AIR AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR BREA

THING. IT MAY ALSO PRODUCE FA TAL CARDIAC ARRHYTHMIAS. INTENTIONALLY SNIFFING FLUOROCARBONS FOR THEIR INTOXICATING EFFECTS HAS LEAD TO HUMAN DEATHS.

Explanation of Carcinogenicity: PRODUCT IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA.

Effects of Overexposure:BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY LEAD TO NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. LIQUID CAN CAUSE DEFATTIN G OF TISSUE

Medical Cond Aggravated by Exposure:SKIN DISEASE - PRODUCT IS A DEFATTING AGENT AND CAN CAUSE DERMATITIS ON PROLONGED EXPOSURE. PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS AGENT.

First Aid:EYE:FLUSH W/ WATER 15 MIN HOLD LIDS OPEN SEE A DOCTOR. SKIN:WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING, AS NEEDED. DO NOT GIVE EPINEPHRINE OR SIM ILAR DRUGS.

INGESTED:DO NO T INDUCE VOMITING. GET IMMEDIATE MEDICAL CARE. IF IRRITATION PERSISTS,OR IS SEVERE,SEE A DOCTOR.

Flash Point:NON-FLAMMABLE Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:MAY EMIT TOXIC FUMES IN FIRE CONDITIONS.

================== Accidental Release Meas

Spill Release Procedures: VENTILATE AREA. DO NOT FLUSH INTO SEWERS. COLLECT ON ABSORBENT MATERIAL AND TRANSFER TO STEEL DRUMS FOR RECOVERY OR DISPOSAL. Neutralizing Agent: NONE

Handling and Storage Precautions:STORE IN A CLEAN, COOL, DRY AND WELL-VENTILATED AREA OF LOW FIRE RISK. PROTECT CONTAINERS FROM PHYSICAL DAMAGE AND KEEP CLOSED.
Other Precautions:TANK-CLEANING PERSONNEL SHOULD USE
ONLY FORMAL TANK
ENTRY PROCEDURE BASED ON RECOGNIZED SAFETY PRINCIPLES. APPLY ALL SAFETY PRECAUTIONS TO EMPTY CONTAINERS AS THEY MAY CONTAIN PRODUCT RESIDUES/VAPORS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED FOR ADEQUATELY VENTED WORK STATIONS. FOR ACCIDENTAL OR NON-VENTILATED SITUATIONS, USE A SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIRATOR, APPROVED BY NIOSH/MSHA. Ventilation:PROVIDE LOCAL E XHAUST AT FILLING ZONES AND OTHER OPERATING SPACES WHERE LEAKAGE IS PROBABLE. MECHANICAL FOR OTHER. Protective Gloves:BUTYL RUBBER, PVA OR NEOPRENE Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES Other Protective Equipment:USE IMPERVIOUS CLOTHING IF THERE IS DANGER OF REPEATED OR PROLONGED CONTACT WITH LIQUID. Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID CONTACT. REMOVE AND WASH CLOTHING PROMPTLY UPON CONTAMINATION. Supplemental Safety and Health NONE

HCC:N1 Boiling Pt:B.P. Text:38F,3.8C Vapor Pres:16.2 PSIG Vapor Density:6.1 Spec Gravity:1.46 Solubility in Water:SLIGHT - 0.01% Appearance and Odor:COLORLESS LIQUID OR VAPOR WITH NO ODOR OR SLIGHT ETHEREAL ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES ALKALI AND ALKALI METALS AND REACTIVE METALS. Stability Condition to Avoid:HEAT SUCH AS OPEN FLAME AND HOT METAL SURFACES.

Hazardous Decomposition Products:DECOMPOSED BY HIGH TEMPERATURES (OPEN FLAMES, GLOWING METAL SURFACES, ETC.) FORMING HYDROCHLORIC AND HYDROFLUORIC ACIDS.

Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Def

ense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.