

COAST WELDING SUPPLY -- OXYGEN,LOX(LIQUID ONLY),GOX(GAS ONLY) -- 6839-00-169-0805

=====
Product Identification
=====

Product ID:OXYGEN,LOX(LIQUID ONLY),GOX(GAS ONLY)

MSDS Date:02/16/1985

FSC:6839

NIIN:00-169-0805

MSDS Number: BHHDX

=== Responsible Party ===

Company Name:COAST WELDING SUPPLY

Address:916 WEST BETTERAVIA RD

City:SANTA MARIA

State:CA

ZIP:93455

Info Phone Num:800-322-2401

Emergency Ph

one Num:800-322-2401

CAGE:7N697

=== Contractor Identification ===

Company Name:COAST WELDING SUPPLY CO

Address:1421 MOUNTAIN VIEW

Box:City:OXNARD

State:CA

ZIP:93030-5106

Country:US

Phone:805-487-0411

CAGE:7N697

=====
Composition/Information on Ingredients
=====

Ingred Name:OXYGEN

CAS:7782-44-7

RTECS #:RS2060000

Other REC Limits:N/K

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:OTHER PREC:USE VALVE TO PRVT BACK FLOW TO CONTR.DON'T USE
FOR CLEANING,DUSTING,POWERING PNEUMATIC T

OOLS. (SEE INGRED #3)

RTECS #:9999999ZZ

Other REC Limits:N/K

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:OTHER PREC:STORE AWAY FROM HEAVILY USED AREAS TO PRVT
DMG.KEEP VALVE CAPS ON CYLINDERS NOT IN USE. (SEE INGRED #4)

RTECS #:9999999ZZ

Other REC Limits:N/K

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:OTHER PREC:NEVER LUBRICATE VALVES OR CYLINDER
CAPS.SEGREGATE FULL AND EMPTY CONTAINERS.

RTECS #:9999999ZZ

Other REC Limits:N/K

OSHA PEL:N/K

ACGIH TLV:N/K

=====
Hazards Id
entification =====

LD50 LC50 Mixture:N/K

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEVERE HAZARDS MAY BE PRESENT WHEN
CONFUSION AND IMPAIRED JUDGEMENT LEAD TO OPERATIONAL ERRORS.INFANTS
EXPOSED TO OXYGEN LEVELS IN EXCESS OF 35-40% MAY SUFFER PERMANENT
VISUAL IMPAIRMENT OR BLINDNESS DUE TO RETROLENTAL FIBROPLASIA.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES/SKIN:LIQ O*2/COLD GAS WILL FRZ TISS & CAN

CAUSE SEV CRYOGENIC BURNS.INGEST:N/A .INHAL:COUGH & CHEST PAINS
FROM PURE O*2 AT 1 ATMOS IN 8-24 HR,FROM 60% CONC IN SEVERAL
DAYS.AT 2 ATMOS S YMP OCCUR IN 2-3 DAYS.>2 ATMOS MAY CAUSE CNS SYMP
(TINGLING FINGERS & TOES,VISUAL & HEARING PROB,CONFUSION, (SEE
SUPP)

Medical Cond Aggravated by Exposure:N/K

=====
First Aid Measures =====

First Aid:EYES/SKIN:IF CRYOGENIC LIQUID OR COLD BOIL-OFF GAS CONTACTS A
WORKER'S SKIN OR EYES,FROZEN TIS

SUES SHOULD BE FLOODED OR SOAKED IN

TEPID WATER (105-115F,41-46C) FOR AT LEAST 15 MIN.DO NOT USE HOT WATER .BURNS WHICH RESULT IN BLISTERING OR DEEPER TISSUE FREEZING SHOULD BE SEEN PROMPLY BY A PHYSICIAN.INGESTION:N/A
.INHALATION:REMOVE TO FRESH AIR .

===== Fire Fighting Measures =====

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .OXYGEN IS NONFLAMMABLE,BUT SUPPORTS AND VIGOROUSLY ACCELERATES COMBUSTION OF FLAMMABLES.

Unusual Fire/Explosion Hazard:SOME MATERIALS WHICH ARE NONCOMBUSTIBLE IN AIR WILL BURN IN THE PRESENCE OF OXYGEN.

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT LIQ O*2 FROM CONTACTING GREASE,OIL,ASPHALT OR COMBUSTIBLES.VENT AREA.FLUSH W/ LRG AMTS OF WATER.DO NOT ENTER AREAS OF HIGH O*2 CONC,WHICH CAN SATURATE CLOTHING,INCREASING IT'S FLAMMABILITY.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:USE/STORE IN WELL-VENT AREA,AWAY FROM FLAM MATL/HEAT/CORR CHEM.DO NOT ENTRAP LIQ IN CLSD SYS.HNDL/MOVE CYLINDERS W/CARE,SECURE WHEN IN USE.

Other Precautions:DO NOT USE O*2 INSTEAD OF COMPRESSED AIR.USE W/ COMPAT MATLS & EQUIP DESIGNED FOR O*2 USE.EXPERTS SHOULD REFILL CYLINDERS.USE A PRESS-REDUCING REGULATOR WHEN CONNECTING TO LOWER PRESS PIPING SYS.OPEN VALVES SLOWLY. (SEE INGRED #2)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:N/A

Ventilation:LOCAL AND GENERAL VENTILATION NECESSARY TO KEEP AIR CONCENTRATION BELOW LEVEL OF CONCERN .

Protective Gloves:LIQ:IMPERMEABLE.GAS CYLINDERS:LEATHER

Eye Protection:CHEMICAL WORKERS GOGGLES .

Work Hygienic Practices:PREVENT CONTACT OF LIQ WITH SKIN.

Supplemental Safety and Health

SPEC GRAV:1.10,AIR=1 (GAS);1.14,WATER=1 (LIQUID).VAP DENS:0.08309 (AIR=1).LIQ DENS:71.21 LBS/CUFT AT BP.FP:-361.8F,-218.8C

EFFECTS OF

OVEREXPOSURE: ABNORMAL SENSATIONS, IMPAIRED COORDINATION, MUSCLE TWITCHING, EPILEPTIC-LIKE SEIZURES. WASTE DISPOSAL METHOD: TO AIR PRODUCTS WITH RESIDUAL PRESSURE, VALVE TIGHTLY CLOSED & VALVE CAP IN PLACE.

===== Physical/Chemical Properties =====

Boiling Point: B.P. Text: -297.3F
Melt/Freeze Point: M.P/F.P Text: N/K
Decomposition Temp: Decomposition Text: N/K
Vapor Density: SEE SUPPLEMENTARY DATA
Specific Gravity: SEE SUPPLEMENTARY DATA
Evaporation Rate & Reference: N/K
Solubility in Water: 3.16% BY VOLUME
Appearance and Odor: GASEOUS OXYGEN IS COLORLESS & ODORLESS. LIQUID OXYGEN IS PALE BLUE & ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
ALL FLAMMABLES, ESPECIALLY PETROLEUM PRODUCTS, ASPHALT, OTHER VOLATILE FLAMMABLES.
Stability Condition to Avoid: MATERIALS THAT BURN IN AIR BURN VIOLENTLY IN ATMOSPHERES OF >25% OXYGEN. SOME MATERIALS BURN IN PURE OXYGEN THAT ARE NONFLAMMABLE IN AIR.
Hazardous Decomposition Products: N/K

===== Disposal Considerations =====

Waste Disposal Methods: EVAPORATE LIQUID IN A WELL-VENTILATED OUTSIDE AREA. VENT GAS TO OUTSIDE. DISPOSAL SITE SHOULD BE AWAY FROM WORK AREAS, OPEN FLAMES, IGNITION SOURCES & COMBUSTIBLES. FLUSH WITH H₂O TO INCREASE EVAPORATION RATE OF LIQUID. DO NOT DISPOSE OF RESIDUAL O₂ IN CYLINDERS. RETURN CYLINDERS (SEE SUPPLEMENTARY DATA)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.