

PPG INDUSTRIES INC CHEMICAL DIVISION -- DX440:DITZ-O WAX & GREASE REMOVER --
7930-01-301-5249

===== Product Identification =====

Product ID:DX440:DITZ-O WAX & GREASE REMOVER

MSDS Date:06/09/1986

FSC:7930

NIIN:01-301-5249

MSDS Number: BHHKT

=== Responsible Party ===

Company Name:PPG INDUSTRIES INC CHEMICAL DIVISION

Address:ONE GATEWAY CENTER

City:PITTSBURGH

State:PA

ZIP:15222-1416

Country:US

Info

Phone Num:412-434-3131 OR 412-963-5822

Emergency Phone Num:304-843-1300

CAGE:93915

=== Contractor Identification ===

Company Name:PPG INDUSTRIES INC CHEMICAL DIVISION

Address:ONE GATEWAY CENTER

City:PITTSBURGH

State:PA

ZIP:15222-1416

Country:US

Phone:304-843-1300

CAGE:93915

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC

CAS:64742-88-7

Fraction by Wt: 35.0%

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE210

0000
Fraction by Wt: 65.0%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CNS EFFECTS LIKE
HEADACHE,DIZZINESS,NAUSEA,VOMITING AND POSSIBLE
UNCONSCIOUSNESS;REDNESS OR
BURNS OF EYES/SKIN
POSSIBLE.CHRONIC:DRYING OF SKIN,DEFATTING OR DERMATITIS,CNS DAMAGE
Explanation of Carcinogenicity:DATA PER MSDS
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUS
CITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:77.0F
,25.0C
Lower Limits:1.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
===== Accidental Release Measures =====

Spill Release Proce

dures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE MATERIAL IF POSSIBLE;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID

PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFE

TY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:352F,178C

Vapor Pres:5.0MMHG

Vapor Density:>1.0

Spec Gravity:0.83

Evaporation Rate & Reference:47(N-BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:FLAMMABLE LIQUID

Percent Volatiles by Volume:100.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS,STRONG MINERAL ACIDS AND ALKALIES.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous

Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER UNIDENTIFIED COMPONENTS.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE
IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States
of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.