View NSN Online: https://aerobasegroup.com/nsn/6850-00-141-2946

TABCO PRODUCTS INC. -- COATING COMPOUND BLACK OXIDE -- 6850-00-141-2946

Product ID: COATING COMPOUND BLACK OXIDE MSDS Date:08/01/1989 FSC:6850 NIIN:00-141-2946 MSDS Number: BHJVH === Responsible Party === Company Name: TABCO PRODUCTS INC. Address:940 WEST 100 SOUTH City:SALT LAKE CITY State:UT ZIP:84104 Country:US Info Phone Num:801-595-0119 **Emergency Phone Num:80** 1-595-0119 CAGE:FO152 === Contractor Identification === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT Address:2275 TUCKER INDUSTRIAL RD Box:City:TUCKER State:GA ZIP:30084 Country:US Phone:770-938-4513/FAX 770-938-3966 Contract Num:SP0450-00-M-D877 CAGE:1MDA6 Company Name: TABCO C D PRODUCTS INC Address:940 W 100 S Box:City:SALT LAKE CITY State:UT ZIP:84104 Country:US Phone:801-595-0119 CAGE:67281 Company Name: TABCO PRODUCTS INC/SALT LAKE CITY, UT 84104 CAGE:FO152

======= Composition/I

nformation on Ingredients =========

Ingred Name:SODIUM HYDROXIDE (SARA III) CAS:1310-73-2 RTECS #:WB4900000 Fraction by Wt: >63% OSHA PEL:2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:SODIUM NITRATE CAS:7631-99-4 RTECS #:WC5600000 Fraction by Wt: >33%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Ac

ute and Chronic:ACUTE: CORROSIVE TO ALL BODY TISSUES W/ WHICH IT COMES IN CONTACT. CHRONIC: SUPERFICIAL DESTRUCTION OF THE SKIN AND OF PRIMARY IRRITANT DERMATITIS. IHALATION OF DUST, SPRAY OR MIST MAY RESULT IN VARYI NG DEGREES OF IRRITATION OR DAMAGE TO THE RESPIRATORY TRACT TISSUES AND AN INCREASED POSSIBILITY OF RESPIRATORY ILLNESS.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposu

re:INHALE: DAMAGE TO THE UPPER RESPIRATORY TRACT AND EVEN TO THE LUNG TISSUE. SKIN: SEVERE BURNS. EYE: SEVERE BURNS WITH DAMAGE TO THE EYE AND EVEN BLINDNESS. INGEST: SEVERE BURNS AND COMPLETE TISSUE PER FORATION OF MUCOUS MEMBRANES OF THE MOUTH, THROAT, ESOPHAGUS, AND STOMACH.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

=

First Aid:INHALATION: REMOVE SUBJECT TO FRESH AIR. EYE: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIA TE MEDICAL ATTENTION.

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG TO CONTROL THE SURROUNDING FIRE.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &

FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:MATERIAL MELTS AT 600 F. HOT MOLTEN CHEMICAL WILL REACT VIOLENTLY WITH WATER, CAUSING SPATTERING AND TOXIC FUMES. REACTS WITH METALS TO GIVE OFF HYDROGEN GAS.
======================================
Spill Release Procedures: FOR SMALL SPILLS, SWEEP UP AND DISPOSE OF IN DOT-APPROVED WASTE CONTAINERS. Neutr
alizing Agent:NONE APPLICABLE FOR THIS MATERIAL
======================================
Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA AWAY FROM MOISTURE, SOLVENTS, ACIDS, AND ORGANIC MATTER. KEEP CONTAINERS CLOSED.
Other Precautions:THIS MATERIAL GENERATES CONSIDERABLE HEAT WHEN DISSOLVED IN WATER. WHEN MIXING WITH WATER ALWAYS ADD CAUSTIC SODA SLOWLY TO WATER AND STIR CONTINUOUSLY. NEVER ADD WATER TO CAUSTIC SODA.
== ======== Exposure Controls/Personal Protection ====================================
Respiratory Protection:RESPIRATION PROTECTION IS NOT REQUIRED UNDER NORMAL USE. USE NIOSH/MSHA APPROVED RESPIRATORS WHERE DUST, MIST OR SPRAY MAY BE GENERATED. Ventilation:USE ADEQUATE LOCAL EXHAUST VENTILATION WHERE DUST, MIST, OR SPRAY MAY BE GENERATED. Protective Gloves:NATURAL OR BUTYL RUBBER
Eye Protection:CHEMICAL SAFETY GOGGLES/FACE SHIELD Other Protective Equipment:SAFETY SHOWER AND EYE BATH. OTHER EQUIPMENT AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT.
Work Hygienic Practices:WASH THROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health
PRODUCT NAME AND PART NUMBER:"COATING COMPOUND BLACK OXIDE, 5010".
======================================
HCC:D1 Boiling Pt:=380.C, 716.F Melt/Freeze Pt:=315.6C, 600.F Spec Gravity:2.15 Solubility in Water:60% Appearance and Odor:WHITE GRA

## NULES-NO ODOR

Stability Indicator/Materials to Avoid:YES WATER, ACIDS, SOLVENTS, ORGANIC MATERIAL. Stability Condition to Avoid:HIGH TEMPERATURES.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. KEEP OUT OF SEWERS, STORM DRAINS, SURFACE WATERS, AND SOIL.

Disclaimer (provided with th

is information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.