View NSN Online: https://aerobasegroup.com/nsn/6850-01-263-8433

AMERICAN GAS AND CHEMICAL COMPANY.,LTD. -- FLAW-FINDER AG-3D-FS PENETRANT 6850-01-263-8433

============= Product Identification ==================

Product ID:FLAW-FINDER AG-3D-FS PENETRANT

MSDS Date:01/03/1989

FSC:6850

NIIN:01-263-8433

MSDS Number: BHKWJ === Responsible Party ===

Company Name: AMERICAN GAS AND CHEMICAL COMPANY., LTD.

Address:220 PEGASUS AVENUE

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Info P

hone Num:201-767-7300

Emergency Phone Num:201-767-7300

Preparer's Name: GEORGE KOSEL, CHIEF CHEM

CAGE:03530

=== Contractor Identification ===

Company Name: AMERICAN GAS AND CHEMICAL COMPANY, LTD

Address: 220 PEGASUS AVENUE,

City:N0RTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

======= Composition/Information on Ingredients ========

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000 Fraction by Wt: 60.0% OSHA PEL:5 MG/M3/10 STEL ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:TRIPHENYL PHOSPHATE

CAS:115-86-6

RTECS #:TC8400000 Fraction by Wt: 1.0% OSHA PEL:3 MG/M3

ACGIH TLV:3 MG/M3; 9192

Ingred Name:PER MANUFACTURER'S MSDS,ITEM CONTAINS NO OTHER HAZARDOUS INGREDIENTS ACCORDING TO THE PROVISIONS GIVEN IN 29CFR1910.2000

RTECS #:9999999ZZ Fraction by Wt: BALANCE

LD50 LC50 Mixture: NONE ESTABLISHE

D BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE: CAUSES IRRITATION OF EYES, SKIN,

RESPIRATORY TRACT; INGESTION MAY CAUSE NAUSEA,

VOMITING, ETC.. INGESTION OF SMALL QUANTITIES IS USUALLY NON-FATAL

UNLESS ASPIRATION OCCURS. ASPIRATION MAY LEAD TO CHEMICAL

PNEUMONITIS.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE LISTED AS AN ANIMAL CARCINOGEN,IT IS NOT

LISTED AS HUMAN CARCINOGEN,PER MFR MSDS INFORMATION.

Effects of Overexposure:INHALATION: DUE TO ITS LOW VOLATILITY, EXPOSURE TO THIS MATERIAL UNDER AMBIENT CONDITIONS IS NOT EXPECTED TO

PRODUCE ADVERSE HEALTH EFFECTS FOLLOWING NORMAL WORKPLACE EXPOSURE:

SKIN: CAN CAUSE SLIGHT IRRITATION; EYES: MAY CAUSE

IRRITATION; INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA,

VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure: NONE CURRENTLY KNOWN.

 First	Δid	Measures	 _

First Aid:INHALATION: REMOVE TO FRESH AIR: SEEK MEDICAL HELP.IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. GIVE OXYGEN IF NEEDED; SKIN AND EYES: FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES. SEEK MEDICAL HELP IF IRRITATION PERSISTS; INGESTION: DO NOT INDUCE VOMITING. IMMEDIATELY CALL A PHYSICIAN.

========== Fire Fighting Measures ================

Flash Point: NONE (AEROSOL)

Extin

guishing Media:REGULAR FOAM, WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS.COOL EXPOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPOR OR FUMES.

Unusual Fire/Explosion Hazard:AEROSOL CONTAINERS MAY BURST/EXPLODE IN HEAT OF FIRE.

======== Accidental Release Measures ===========

Spill Release Procedures: USE PROPER PERSONAL PROTECTION: REMOVE IGNITION SOURCES: RECOVE

R FREE LIQUID; USE SUITABLE INERT ABSORBENT SUCH AS SAND, CLAY, ETC. TO ABSORB LIQUID. KEEP MATERIAL OUT OF SEWERS/WATER WAYS.LG SPILLS MAY BE P ICKED UP BY VACUUM PUMPS, SHOVELS & PLACEIN DRUMS.

=========== Handling and Storage =============

Handling and Storage Precautions:STORE IN A COOL DRY PLACE BELOW 120F.
DO NOT PUNCTURE OR DAMAGE CONTAINERS. DO NOT STORE OR HANDLE NEAR
HEAT,SPARKS OR OXIDANTS.KEEP PLAINLY LABELED.

Other Precautions: DO NOT PRESSURIZE,

CUT, WELD, BRAZE, SOLDER, DRILL,

GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION, THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.DO NOT ATTEMT TO CLE AN SINCE RESIDUE IS DIFFICULT TO REMOVE.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF NEEDED.

Ventilation: GOOD, GENRAL VENTILATION IS SUFFICIENT.

Protective Gloves: NON ABSORBENT GLOVES

Eye Protectio

n:SAFETY GLASSES

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING IF NEEDED TO AVOID CONTAMINATING REGULAR CLOTHING.EYE-WASH FAC

Work Hygienic Practices: ADHERE TO GENERAL INDUSTRIAL HYGIEN PRACTICE AT THE WORKPLACE.

Supplemental Safety and Health

NSN IS FOR PENETRANTS OF TYPE I, METHOD C, LEVEL 3 OF MIL-I-25135, REV E. IN ACCORDANCE WITH QPL-25135-15, FLUORO-FINDER AG-3A-FW, AND FLAW-FINDER AG-3D-FS PENTRANTS ARE TYPE I, METHOD C AND LEVEL 3 P

RODUCTS. THIS ENTRY DESCRIBES FLUORO-FINDER AG-3D-FS PENETRANT. SEE PNI B,THIS NSN, FOR FLAW-FINDER AG-3A-FW PENETRANT.

======== Physical/Chemical Properties ===========

HCC:V1

Boiling Pt:B.P. Text:N/R(AEROSOL

Vapor Pres:1.0(AIR=1 Spec Gravity:0.98 (BULK)

Evaporation Rate & Damp; Reference: 0.1 (N BUAC=1) (BULK)

Solubility in Water: NEGLIGIBLE

Appearance and Odor:BULK PRODUCT: YELLOW-GREEN LIQUID;MILD ODOR

Percent Volatiles by Volume:>95%

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENT.

Stability Condition to Avoid: EXTREME HEAT

Hazardous Decomposition Products:BURNING CAN PRODUCE CARBON DIOXIDE AND/OR CARBON MONOXIDE.

======= Disposal Considerations ============

Waste Disposal Methods:WASTE PRODUCT SHOULD BE INCINERATED OR DISPOSED OF IN AN APPROVED DISPOSAL SITE OR FACILITY.CAN BE RECLAIMED AND RECYCLED.ASSURE CONFORMITY WITH ALL APP LICABLE LOCAL,STATE AND FEDERAL DISPOSAL REGULAT IONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the

