

GLIDDEN DURKEE DIV OF SCM -- TTE 516A COMPL L QD OD 921 G 2105 X -- 8010-00-297-2116
===== Product Identification =====

Product ID:TTE 516A COMPL L QD OD 921 G 2105 X

MSDS Date:06/10/1975

FSC:8010

NIIN:00-297-2116

MSDS Number: BHLST

=== Responsible Party ===

Company Name:GLIDDEN DURKEE DIV OF SCM

Address:900 UNION COMMERCE BLDG

City:CLEVELAND

State:OH

ZIP:44115

Info Phone Num:(216) 771-5121

Emerg

ency Phone Num:(216) 771-5121

CAGE:GO866

=== Contractor Identification ===

Company Name:GLIDDEN CO MEMBER OF ICI WORLD PAINTS

Address:925 EUCLID AVE

Box:15049

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:216-344-8000

CAGE:72818

Company Name:GLIDDEN DURKEE DIVISION OF SCM

CAGE:GO866

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by

Wt: 0.2%
Other REC Limits:A2 CARCINOGEN
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1%
Other REC Limits:300 MG/CUM
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LACTOL SPIRITS
Fraction by Wt: 23%
OSHA PEL:250 PPM

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 15%
Other REC Limits:STEL 400 PPM
OSHA PEL:300 PP
M/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 4%
Other REC Limits:100 PPM
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF EYES, SKIN,

& RESPIRATORY TRACT. SKIN: REPEATED/PROLONGED CONTACT CAUSE POSSIBLE DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: REPEATED/PROLONGED CONTACT CAUSE POSSIBLE DERMATITIS. INHALATION: IRRITATION OF EYES, SKIN, & RESPIRATORY TRACT.

Medical Cond Aggravated by Exposure:DERMATITIS

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE PERSON TO WELL VENTILATED AREA. RESTORE BREATHING. GET MED ATTN. SKIN: WIPE WITH CLEAN CLOTH. WASH THOROUGHLY W/SOAP & WATER. EYE: FLUSH THOROUGHLY WITH WATER. GET MED ATTN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:38F

Lower Limits:0.9%

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS EXPOSED TO EXTREME HEAT OR FIRE TO PREVENT BUILD UP/AUTOIGNITION/EXPLOSION.

Unusual Fire/Explosion Hazard:

KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME.

DON'T APPLY TO HOT SURFACES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. MOP SPILLS W/INERT ABSORBENT. BURN SWEEPINGS IN A SAFE AREA.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE