

PLASTI-KOTE CO., INC. -- ENAMEL AEROSOL SPRAY PAINT BLACK 17038 -- 8010-00-079-3752
===== Product Identification =====

Product ID:ENAMEL AEROSOL SPRAY PAINT BLACK 17038

MSDS Date:12/30/1986

FSC:8010

NIIN:00-079-3752

MSDS Number: BHMCK

=== Responsible Party ===

Company Name:PLASTI-KOTE CO., INC.

Address:1000 LAKE ROAD

City:MEDINA

State:OH

ZIP:44256

Country:US

Info Phone Num:(216) 725-4511

Emergenc

y Phone Num:(216) 725-4511

CAGE:HO182

=== Contractor Identification ===

Company Name:PLASTI-KOTE CO., INC.

CAGE:HO182

Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

Address:1000 LAKE ROAD

Box:City:MEDINA

State:OH

ZIP:44256

Country:US

Phone:330-725-4511

CAGE:07708

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 30-40%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rp

t Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5-10%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 5-10%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:DIACETONE ALCOHOL

(VP .8 MM HG @ 20C)

CAS:123-42-2

Fraction by Wt: 5-6%

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

Ingred Name:ME

THYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 5%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING AND INHALING THE CONTENTS MAY BE HARM

FUL OR FATAL.

Effects of Overexposure:INHALING CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE,NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. EYE CONTACT CAN CAUSE SEVERE IRRITATION, REDNESS, TE ARING, BLURRED VISION. SWALLOWING CANCAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA.SKIN IRRITANT TOO.

Medical Cond Aggravated by Exposure:CAN CAUSE ALLERGIC RESPIRATORY AND/OR SKIN REACTION.

=====
First Aid Measures =====

First Aid:INHALED:REMOVE TO FRESH AIR. GIVE CPR AND OXYGEN IF NECESSARY. SEEK MED. HELP. EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE OCCASSIONALLY HOLDING EYELIDS OPEN. GET MED. ATTN. IF SWALLOWED: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET,AND GET MEDICAL ATTENTION/POISON CONTROL CENTER. SKIN: WASH WITH SOAP AND WATER OR VARIOUS HAND CLEANERS, AND WASH CLOTHING BEFORE RE-USE.

=====
Fire Fighting Measures =====

Flash Point:NR

Lower Limits:1.0

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL CLOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. USE S.C.B.A. WITH FULL FACE PIECE.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE AND/OR AUTOIGNITE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL/BE MOVED BY VENTILATION TO IGNITION SRC

=====
Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO A CLOSED CONTAINER.

=====
Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120F OR IN DIRECT SUNLIGHT OR NEAR HEAT OR OPEN FLAMES. DO NOT PUNCTURE OR INCI

NERATE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR CASUAL/OCCASSIONAL USE-OPEN WINDOWS AND DOORS OR USE OTHER MEANS TO ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. IF OVEREXPOSURE SYMPTOMS OCCUR, WEAR NIOSH/MSHA RESPIRATORY PROTECTION O R LEAVE THE AREA.

Ventilation:FOR REGULAR/CONTINUOUS USE-PROVIDE SUFFICIENT MECHANICAL AND/OR LOCAL EXHAUST VENTILATION.

Protective Gloves:CHEMICAL RESISTANT GLOVES/NEOPRENE

Eye Pr

tection:CHEMICAL SPLASH GOGGLES

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. AS WITH ALL CHEMICALS, MINIMIZE PERSONAL CONTACT AND BREATHING OF VAPORS

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:133 - 331F

Melt/Freeze Pt:M.P/F.P Text:MIN 1500F

Vapor Density:> AIR

Spec Gravity:< 1

Evaporation Rate & Reference:SECT.1 PROD.>1/PROPELNT