View NSN Online: https://aerobasegroup.com/nsn/8010-00-297-0590

PRATT & LAMBERT, INC. -- ENAMEL ALKYD SG BLUE 25053 ID 745506 -- 8010-00-297-0590

Product ID:ENAMEL ALKYD SG BLUE 25053 ID 745506

MSDS Date:06/05/1989

FSC:8010

NIIN:00-297-0590

MSDS Number: BHMLQ === Responsible Party ===

Company Name: PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS

ZIP:67201 Country:US

Preparer's Name: W.A. ELLISON

CA

GE:FO127

=== Contractor Identification ===

Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS

(VAPOR PRESSURE 2 MM HG @ 20 DEC C.)

CAS:64742-88-7 Fraction by Wt: 40%

OSHA PEL:500 PPM 2950 MG/CU M ACGIH TLV:100 PPM 525 MG/CU M

Ingred

Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000

Fraction by Wt: 102 F/38.89 C

Extinguishing Media:CLASS B FIRE EXTINGUISHERS TO EXTINGUISH FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE INNEFECTIVE, BUT MAY BE USED TO PREVENT PRESSURE BUILD-UP. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE

FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

======== Accidental Release Measures ===========

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE IGNITION SOURCES. DIKE & CONTAIN W/INERT MATERIAL. TRANSFER LIQ TO COVERED METAL CONTAINERS FOR RECOVERY OR REMOVE W/INERT ABSORBENT. USE NON-SPARKING TOOLS. PLACE ABSO RBENT DIKING MATERIAL CON COVERED METALCONTAINER.

= Handling and Storage ===========

Handling and Storage Precautions: DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DONOT TAKE INTERNALLY. CLOSE CONT AFTER EACH USE.
DONOT BREATHE SANDING DUST. EMPTY CONTAINERS SHOULD NOT BE WASHED
AND REUSED. DONOT WELD/BRAZE/CUT ON EMPTY CONTAINERS. NEVER USE
PRESSURE TO EMPTY. D RUM IS NOT A PRESSURE VESSEL.


===== Exposure Controls/Personal Protection ========

Respiratory Protection: IN RESTRICTED VENTILATION AREAS A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAYBE REQD. CERTAIN COND SUCH AS SPRAYING A MECHANICAL PREFILTER MAY ALSO BE REQUIRED. EXP TO ORGANIC CHEM SUCH AS THOSE CONTAINED HEREIN MAYNOT REQ RESP PROTECT

Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO MAINTAIN CONCENTRATIONS.

Protective Gloves: SOLVENT IMPERMEABLE Eye Protection: WEAR SAFETY SPECTACLES

Other Protec



======= Disposal Considerations ============

Waste Disposal Methods: DISPOSE IAW FEDERAL, STATE AND LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FL AMMABLE

MATERIALS. DISPOSE ONLY IAW STA TE, FEDERAL AND LOCAL LAWS. CLASSIF D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to ve rify and

assume responsibility for the suitability of this information to their particular situation.