

ASPEN PAINTS -- ACRYLIC LATEX PAINT, EXTERIOR YELLOW 33727 -- 8010-00-418-4668

=====  
Product Identification  
=====

Product ID:ACRYLIC LATEX PAINT, EXTERIOR YELLOW 33727

MSDS Date:02/01/1989

FSC:8010

NIIN:00-418-4668

MSDS Number: BHMPG

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Country:US

Info Phone Num:(206) 682-4603

Emer

gency Phone Num:(303) 573-1014

Preparer's Name:DOUGLAS KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: < 5%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Na

me:AMMONIUM HYDROXIDE (SARA III)

CAS:1336-21-6

RTECS #:BQ9625000

Fraction by Wt: < 1%

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:INHAL: ADVERSE HEALTH EFFECTS FROM VAPORS/SPRAY MISTS IN POORLY VENTED AREAS MAY CAUSE IRRITATION OF THE MUCOUS MEMBRANES OF THE NOSE/THROAT/RESPIRATORY TRACT & HEADACHE & NAUSEA.

SKIN & EYE: PROLONGED /REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION, DIRECT CONTACT MAY RESULT IN EYE IRRITATION

===== First Aid Measures =====

First Aid:INHAL: REMOVE SUBJECT TO FRESH AIR. EYE & SKIN: PROMPTLY & THOROUGHLY WASH EYES W/WATER AT LEAST 15 MIN, CONSULT A DOCTOR IF IRRITATION PERSISTS. REMOVE CONTAMINATED CLOTHING, WASH SKIN THOROUGHLY WITH SOAP & WATER, WASH CLOTHING BEFORE REUSE

===== Fire

Fighting Measures =====

Flash Point:NONE

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:PAINT WILL NOT BURN UNTIL WATER HAS EVAPORATED. FOR RESIDUALSOLIDS: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL OR WATER FOG

Fire Fighting Procedures:CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WATER MAY BE USED TO COOL UNRUPTURED CONTAINER. AVOID SPREADING OF BURNING LIQ W/WATER USED TO COOL

Unusual Fire/Explosion Hazard:CAN SPLATTER IF TEMP EXCEED BOILING POINT

NT. RESIDUAL SOLIDS CAN BURN, GIVING OFF CARBON

MONOXIDE/DIOXIDE, ETC. SELF CONTAINED BREATHING APPARATUS MAY BE NEEDED

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID. PICK UP REMAINING LIQUID WITH ABSORBANT MATERIAL & PLACE INTO CONTAINER FOR DISPOSAL. WASH AREA WITH WATER & DETERGENT. DO NOT WASH INTO PUBLIC WATER SOURCE.

===== Handling and Storage =====

Handling and S

Storage Precautions: STORE AT ROOM TEMP TO PROLONG STORAGE LIFE. KEEP FROM FREEZING SO PRODUCT DOES NOT COAGULATE. DO NOT APPLY WHEN TEMP IS BELOW 50F/10C.

Other Precautions: SHAKE OR STIR WELL BEFORE USING. DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT WITH SKIN OR BREATHING OF SPRAY MIST. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN. THESE PRODUCTS CONTAIN NO LEAD PIGMENTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:

USE ORGANIC VAPOR CANISTER OR SUPPLIED-AIR RESPIRATORY PROTECTION WHEN TLV IS EXCEEDED.

Ventilation: SUFFICIENT MECHANICAL VENTILATION WITH EXPLOSION PROOF EQUIPMENT TO MAINTAIN EXPOSURE LEVEL BELOW TLV.

Protective Gloves: IMPERMEABLE GLOVES

Eye Protection: SPLASH GOGGLES OR FACE SHIELD

Work Hygienic Practices: USE PROTECTIVE CREAM WHERE SKIN CONTACT IS LIKELY. TO PREVENT REPEAT/PROLONGED CONTACT WEAR IMPERVIOUS CLOTHING/BOOTS

Supplemental Safety and Health

WASH HANDS BEFORE E

EATING OR USING THE WASHROOM. SMOKE IN SMOKING AREA ONLY.

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 212 F

Vapor Density: < AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: COMPLETE

Appearance and Odor: THICK LIQUID, WHITE AND VARIOUS COLORS, SLIGHT AMMONIA ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: HIGH TEMPERATURE

E

Hazardous Decomposition Products: WHEN PRODUCT IS HEATED TO DECOMP IT MAY PRODUCE FUMES WHICH CONTAIN CARBON MONOXIDE/DIOXIDE, ETC.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for us

e by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.