

PRATT & LAMBERT, INC. -- LACQUER ACRYLIC N/C CAM BLK 37038 ID792702 -- 8010-00-527-2884

=====
Product Identification
=====

Product ID:LACQUER ACRYLIC N/C CAM BLK 37038 ID792702

MSDS Date:12/13/1988

FSC:8010

NIIN:00-527-2884

MSDS Number: BHMQX

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A

. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES

Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: REPEATED EXPOSURE TO CRYSTALLINE SILICA MAY CAUSE PNEUMOCONIOSIS, A PROGRESSIVELY DISABLING LUNG DISEASE. OVEREXPOSURE TO XYLENE MAY CAUSE INJURY TO LIVER, KIDNEYS & BLOOD. PROLONGED/REPEATED OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. DELIBERATE MISUSE OF CONTENTS MAY BE HARMFUL OR FATAL.

Effects of Overexposure: INGEST: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING &

DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHAL: MAY CAUSE IRRITATION TO NOSE, THROAT & ACUTE NERVOUS SYSTEM DEPRESSION. EYE: IRRITATION SKIN: MAY CAUSE DEFATTING & IRRITATION OF THE SKIN.

Medical Conditions Aggravated by Exposure: PREEXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA

=====
===== First Aid Measures =====

First Aid: INGEST: CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

INHAL: REMOVE TO FRESH AIR IMMEDIATELY, GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM/QUIET, GET MEDICAL ATTENTION IMMEDIATELY. EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. LIFTING EYELIDS, GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA W/SOAP & WATER, GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point: 24F/-4.44C

Extinguishing Media: NFPA CLASS B FIRE EXTINGUISHER DESIGNED TO EXTINGUISH FLAMMABLE LIQUID

FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO PREVENT PRESSURE BUILD-UP. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATL. TRANSFER LIQ TO COVER METAL CONTAINER. USE NON SPARKING TOOLS. PREVENT CONTAMINATION OF SEWER,STREAMS, & GROUNDWATER W/SPILLED MATL OR USED ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120 DEGREES F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE SANDING DUST. DO NOT WASH & REUSE CONTNRS FOR ANY PURPOSE. DO NOT WELD, BRAZE OR CUT ON EMPTY CONT. NEVER USE PRESSURE TO EMPTY. CONTAINER SHOULD BE GROUNDED & BONDED TO THE RECEIVING CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SPRAYING, USE NIOSH APPROVED MECHANICAL RESPIRATOR. RESTRICTED AREAS USE NIOSH APPROVED CHEMICAL CARTRIDGE/MECHANICAL FILTER. CONFINED AREA USE NIOSH APPROVED AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL DILUTION & LOCAL EXHAUST VENTILATION.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:WEAR SAFETY SPECTACLES WITH SIDE SHIELDS

Other Protective Equipment:NOT LIKELY TO BE NEEDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175-281F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles

by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS, AND FLAME

===== Disposal Consi

derations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA FACILITY. DO NOT
INCINERATECLOSED CONTAINERS. DISPOSE IN ACCORDANCE WITH
FEDERAL, STATE, & LOCAL REGULATIONS. CONTAMINATED ABSORBENT MAY BE
DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly
or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.