View NSN Online: https://aerobasegroup.com/nsn/8010-00-664-6302

## CHEMRAY COATINGS, CORP. -- PRIMER FOR WOOD AND METAL -- 8010-00-664-6302

Product ID:PRIMER FOR WOOD AND METAL

MSDS Date:11/01/1989

FSC:8010

NIIN:00-664-6302

MSDS Number: BHMSY === Responsible Party ===

Company Name: CHEMRAY COATINGS, CORP.

Address: 209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ ZIP:07033 Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:201-245-1111

CAGE:OBRN9

=== Contractor Identification ===

Company Name: CHEMRAY COATING CORP

Address: 209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ ZIP:07033 Country:US

Phone:201-245-1111

CAGE:33832

Company Name: CHEMRAY COATINGS CORP.

Address: 209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ ZIP:07033 Country:US

Phone:800-924-9300

CAGE:OBRN9

====== Composition/Information on Ingredients ========

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000


Fraction by Wt:

39% OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293 ============= Hazards Identification ======================== Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Health Hazards Acute and Chronic:OVEREXPOSURE - NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION Effects of Overexposure: OVEREXPOSURE - NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION Medical Cond Aggravated by Exposure: NONE GENERALLY KNOWN First Aid:EYE: FLUSH W/WATER 15 MIN. UNTIL IRRI SUBSIDES, IF IRRI PERSISTS CALL PHYSICIAN.SKIN: REMOVE CONTAMINATED CLOTHING & WASH THROUGHLY WITH SOAP & WATER. INHAL: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL PHYSICIAN.INGST: DO NOT INDUCE VOMITING CALL PHYSICIAN. Flash Point Method:SCC Flash Point:103 F/40 C Lower Limits:0.9 **Upper Limits:7** Extinguishing Media: CARBON DIOXIDE, FOAM, WATER FOG, DRY **CHEMICAL** Fire Fighting Procedures: USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS AND FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS

========= Accidental Release Measures ===========

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT SPARKS& OPEN FLAMES. ADD ABSORBENT (SAND, EARTH, ETC.) VENT AREA. IF LG S



========= Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES CAN REACT W/OXIDIZING MATERIAL WHEN

HEATED TO DECOMPOSTION.
Stability Condition to Avoid:HIGH TEMPERATURE
Hazardous Decomposition Products:CARBON MONOXIDE

====== Disposal Considerations ==========

Waste Disposal Methods: ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REG DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY. DISPOSE IN COMFORMITY WITH STATEAND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated f or use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.