

PRATT & LAMBERT, INC. -- ENAMEL ALKYD SG GRAY 26134, ID745612 -- 8010-00-680-2410
===== Product Identification =====

Product ID:ENAMEL ALKYD SG GRAY 26134, ID745612

MSDS Date:03/31/1986

FSC:8010

NIIN:00-680-2410

MSDS Number: BHMTG

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733
-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE

CAS:13

09-37-1
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:MINERAL SPIRITS
(VAPOR PRESSURE 2 MMHG @ 20C)
CAS:64475-85-0
RTECS #:PY8240000
OSHA PEL:500 PPM 2950 MG/CU.M
ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC. ORGANIC CMPD 3.8 LB/GAL LESS WATER & NPRS* 456 G/L
LESS WATER VOC. 8.8 LB/GAL SOLIDS 1056 G/L SOLIDS CALCU
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO

OSHA:NO

Health Hazards Acute and Chronic:ASPIRATION OF MATL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHAL MAY CAUSE ACUTE NERVOUS SYSTEM DEPRESSION. REPEATED EXPOSURE TO CRYSTALLINE SILICA MAY CAUSE PNEUMOCONIOSIS, A PROGRESS. DISABLING LUNG DISEASE.INTENTIONAL MISUSE MAY BE HARMFUL OR FATAL.

Effects of Overexposure:EYE: IRRITATION; SKIN: DEFATTING & IRRITATION

INHAL: NOSE,THROAT IRRITATION,HEADACHE, DIZZINESS, CONFUSION, NAUSEA,UNCONSCIOUSNESS,

& EVEN ASPHYXIATION.INGEST: GASTROINTESTINAL IRRIT., NAUSEA, VOMITING, & DIARRHEA.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR, LIFTING EYELIDS FOR 15 MINS.,GET MEDICAL ATTN. SKIN: WASH AFFECTED AREA W/SOAP & WATER, GET MEDICAL ATTENTION INHAL: REMOVE TO FRESH AIR IMMEDIATELY, GIVE ARTIFICIAL RESPIRATION IF NECESSARYKEEP WARM & QUIET, GET MEDICAL ATTENTION IMMEDIATELY.

INGS

T: INDUCE VOMITING IMMED.,GIVE 2 GLS OF WTR USE FINGER, GET MEDICAL ATTNT.

=====
===== Fire Fighting Measures =====

Flash Point:80F/26.67C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFER-RED FOR LARGE FIRES.

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SCBA. WATER MAY BE INEFFECTIVE,MAY BE USED TO COOL EXPOSED CONTNRS TO PREVENT PRESS BUILDUP & POSS AUTO IGN. WHEN EXPSD TO EXTRM HEAT.

Unusual Fire/Explosion Hazard

:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELEC. EQUIP,SPARKS, & FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE & CONTAIN SPILL W/INERT MATL. USE ONLY NON SPARKING TOOLS. PLACE ABSORBENT DIKING MATL IN COVERED METAL CONT-AINER. PREVENT CONTAMINATION OF SEWERS,STREAMS,AND GROUNDWATER W/SPILLED MATL OR USED ABSO

RBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QTYS
IN COMPLIANCE WITH OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH
USE. NEVER USE PRESSURE TO EMPTY

Other Precautions:DO NOT TAKE INTERNALLY. EMPTY CONTAINERS MUST NOT BE
WASHED & REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED &
BONDED TO THE RECEIVING CONTAINERS. DO NOT WELD, BRAZE OR CUT ON
EMPTY CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREAS USE NIOSH APPROVED CHEMICAL
CARTRIDGE/MECHANICAL FILTER. CONFINED AREAS USE A NIOSH
APPROVED AIR SUPPLIED RESPIRATOR. WHEN SPRAYING
IN WELL VENTILATED AREAS USE NIOSH APPROVED MECHANICAL FILTER RESP

Ventilation:GENERAL DILUTION AND LOCAL EXHAUST

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES;FACESHIELD WHEN SPRAYING

Other Protective Equipment:NOT LIKELY
TO BE NEEDED.

Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:244-395F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:57

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:BURNING INCLUDING WHEN HEATED BY

WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE ONLY IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.