View NSN Online: https://aerobasegroup.com/nsn/8010-00-753-4550 PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS GRN 14050 ID742404 -- 8010-00-753-4550 Product ID:ENAMEL ALKYD GLOSS GRN 14050 ID742404 MSDS Date:03/23/1988 FSC:8010 NIIN:00-753-4550 MSDS Number: BHMVB === Responsible Party === Company Name: PRATT & LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Preparer's Name: W.A. ELLISON CAGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

========== Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:

YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONG/REPEATED OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE MAY BE HARMFUL OR FATAL. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHIC H CAN BE FATAL. HIGH CONCENTRATIONS MAYCAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity: MANUFACTURER CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN.

Effe

cts of Overexposure:INGST: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. INHAL: NOSE/THROAT IRRITATION,HDACHES,DIZZINESS,NAUSEA, AND CONFUSION. EYE: IRRITATIONSKIN: IRRITATION AND DEFA TTING OF SKIN

First Aid:INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY INHAL: REMOVE TO FRESH AIR IMMED.,GIVE ARTIFICIAL RESP. IF NECESSARY,KEEP WARM & QUIET,GET MED ATTN IMMED.; EYE: FLUSH W/L

ARGE AMTS OF WATER, LIFTING EYELIDSFOR AT LEAST 15 MIN.
GET MED ATTN.; SKIN: REMOVE CONTAMINATED CLOTHES. WASH AFFECTED AREA W/SOAP & WTR. GET MEDICAL ATTENTION.

========== Fire Fighting Measures ===============

Flash Point Method:SCC Flash Point:> 102 F/38.89 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRES. POLYMER FOAM PERFER

Fire Fighting Procedures: SELF CONTAIN BREATH APPARATUS. WTR MAY BE

INEFFECT, USED TO COOL TO PREVENT PRESSURE
BUILD-UP/AUTO-IGNITE/EXPLOSION FROM HEAT. IF WTR USED, FOG NOZZLES
PREFERR

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELEC. EQUIP, SPARKS, & FLAME.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

======== Accidental Release Measures ===========

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATERIAL. USE NON SPA

ABSORBENT DIKING MATERIALS IN COVERED METAL CONTAINER FOR DISPOSAL. PREVENT SEWERS, STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORB
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LG QTYS INCOMPLIANCE W/OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH USE. NEVER USE PRESSURE TO EMPTY CONTAINER. Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDI NG DUST.
EMPTY CONTAINERS MUST NOT BE WASHED AND REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINERS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:RESTRICTED AREAS USE A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. FOR SPRAYING USE A MECHANICAL PREFILTER. IN CONFINED AREAS USE A NIOSH/MSHA APPRO VED AIR SUPPLIED RESPIRATOR. Vent ilation:GENERAL DILUTION AND LOCAL EXHAUST Protective Gloves:SOLVENT IMPERMEABLE GLOVE Eye Protection:WEAR SAFETY SPECTACLES Other Protective Equipment:NONE LIKELY NEEDED Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:280-388 F Vapor Density:> AIR Evaporation Rate & Description Rate & Description Reference: SLOWER THAN ETHER Percent Volatiles by Volume:62
======== Stability and Reactivity Data =========
Stability Indicator/M

RKING TOOL ONLYPLACE

aterials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS
Stability Condition to Avoid:EXCESSIVE HEAT & SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDE WHEN HEATED BY
WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF INACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATION. DO NOT INCI
NERATE CLOSED CONTNRSINCINERATE ONLY
IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.