

CHEMEX PAINT AND COATING -- CHEM PRO -- 8010-00-823-7962

=====
Product Identification
=====

Product ID:CHEM PRO
MSDS Date:02/03/1988
FSC:8010
NIIN:00-823-7962
MSDS Number: BHMWF
=== Responsible Party ===
Company Name:CHEMEX PAINT AND COATING
Address:2822 35TH STREET
City:TAMPA
State:FL
ZIP:33605
Country:US
Info Phone Num:813-248-6104
Emergency Phone Num:813-248-6104
CAGE:OA701
=== Contractor Identification ===
Company Name:CHEMEX PAINT & COATINGS, INC.
CAGE:0A701
Company Name:CHEMEX PAINT AND COATING
Address:2822 35TH STREET
City:TAMPA
State:FL
ZIP:33605
Country:US
Phone:(813) 248-6104
CAGE:OA701

=====
Composition/Information on Ingredients
=====

Ingred Name:ACRYLIC POLYMER
OSHA PEL:NE
ACGIH TLV:NE

Ingred Name:TITANIUM DIOXIDE
CAS:1317-80-2
ACGIH TLV:10 MG/CU.M.

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES S

kin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE

Effects of Overexposure:INHAL: VAPOR OR SPRAY MIST CAN CAUSE HEADACHE,
NAUSEA, IRRITATION OF NOSE, THROAT AND LUNGS. EYES: POSSIBLY IRRITATING
TO EYES. SKIN: SLIGHTLY IRRITATING TO SKIN. AND INGESTION:
PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION TO THE
DIGESTIONTRACT.

Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====
=====

First Aid:MOVE SUBJECT TO FRESH AIR. FLUSH EYES WITH LARGE AMOUNTS OF
WATER. WASH SKIN AREAS WITH SOAP AND WATER.

=====
===== Fire Fighting Measures =====
=====

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NA

Fire Fighting Procedures:NA

Unusual Fire/Explosion Hazard:MATERIAL IS NON COMBUSTIBLE

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY.
DIKE & CONTAIN SP
ILL WITH INERT MATERIAL. TRANSFER LIQ TO CONTAINER
FOR RECOVERY/DISPOSAL & SOLID DIKING MATERIAL TO SEPARATE CONT. FOR
DISPOSAL. PREVENT CONTAM OF MUNICIPAL SEWERS & OPEN BODIES OF
WATER

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:KEEP FROM FREEZING.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:NONE REQUIRED IF VENTILATION IS ADEQUATE

Ventilation:EXT. NORM

AL. LOCAL EXHAUST INDOORS. MECHANICAL INDOORS.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:NONE

Work Hygienic Practices:WASH AFTER USE

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 F

Vapor Pres:17

Vapor Density:1 WATER

Spec Gravity:1.42

Solubility in Water:DILUTABLE

Appearance and Odor:WHITE-LATEX PAINT

===== Stability and Reactivity Data =====

=====

NA

Stability Condition to Avoid:NA

Hazardous Decomposition Products:NA

===== Disposal Considerations =====

Waste Disposal Methods:COAGULATE THE PAINT BY THE STEPWISE ADDITION OF FERRIC CHLORIDE & LIME. REMOVE THE CLEAR SUPERNATANT LIQ & FLUSH TO A CHEM SEWER. LANDFILL THE SOLIDS & THE CONTAMINATING MATERIAL ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This inf

ormation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.