

PRATT & LAMBERT, INC. -- LACQUER ACRYLIC RED 11136, ID794104 -- 8010-00-935-7063

=====  
Product Identification  
=====

Product ID:LACQUER ACRYLIC RED 11136, ID794104

MSDS Date:10/14/1988

FSC:8010

NIIN:00-935-7063

MSDS Number: BHMYR

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISON

CAGE

:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR  
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

ingred Name:TOLUENE

(SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

ingred Name:VOC. ORGANIC CMPD 5.2 LB/GAL LESS WATER & NPRS\* 624 G/L

LESS WATER VOC. 19.4 LB/GAL SOLIDS 2328 G/L SOLIDS CALCU

RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chron

ic:LIQUID MATL MAY BE ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS. TOLUENE MAY CAUSE LIVER DAMAGE. ASPIRATION OF MATL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. HI CONCENTN MAY CAUS E ACUTE CENTRAL NERVOUS SYSTEM DEPRESS.OVEREXPSR TO SOLVENT W/PERMNT BRAIN & NERVS DAMAGE. MISUSE CAN BE HARMFUL/FATAL.

Explanation of Carcinogenicity:CHROMIUM/CHROMIUM COMPOUNDS, & LEAD CHROMATE ARE LISTED AS POTENTIAL CARCINOGENS

Effects of Overexposure:EYE: MAY CAUSE IRRITATION; SKIN: MAY CAUSE

IRRITATION AND DEFATTING OF SKIN INHAL: NOSE/THROAT IRRIT., HEADACHES, DIZZINESS, NAUSEA, AND CONFUSION INGST: GASTROINTESTINAL IRRITATION, NAUS EA, AND VOMITING.

Medical Cond Aggravated by Exposure:PREEXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO LEAD.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR FOR 15 MINS, LIFTING EYELIDS, GET MEDICAL ATTENTIONSKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE

CONTAMINATED CLTHS,GET MEDICAL ATTNINHAL: REMOVE TO FRESH AIR IMMEDIATELY,G IVE ARTIFICIAL RESPIRATION,KEEP WARM ANDQUIET,GET MEDICAL ATTENTION IMMEDIATELY

INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN OR HOSPITAL IMMEDIATELY

===== Fire Fighting Measures =====

Flash Point:24F/-4.44C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFER-RED FOR LARGE FIRES.

Fire Fighting Proce

dures:SHOULD WEAR SCBA. WATER MAY BE INEFFECTIVE, BUT MAYBE USED TO COOL EXPSD CONTNRSTO PREVENT PRESS. BUILDUP W/EXPSD TO EXTRM HEAT. FOG NOZZLES ARE PREFERRED W/WTR

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. WARNING!! FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATL. USE

ONLY NON SPARKING TOOLS. PLACE  
ABSORBENT DIKING MATL IN COVERED METAL CONTAINERS FOR DISPOSAL.  
PREVENT CONTAMINATION OF SEWERS, STREAMS, & GROUNDWATER W/ SPILLED  
MATERIAL ABSORBENT

=====  
===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 95F. STORE LG QTY  
IN COMPLIANCE W/ OSHA 29CFR 1910.106. CLOSE CONTAINER AFTER EACH USE.  
NEVER USE PRESSURE TO EMPTY CONTAINERS.

Other Precautions: DO NOT TAKE INTERNALLY. EMPTY CONTAINERS MUST NOT BE  
WASHED & REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE  
GROUNDED/BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE, OR  
CUT ON EMPTY CONTAINER.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: RESTRICTED AREAS USE A NIOSH APPROVED CHEMICAL  
CARTRIDGE RESPIRATOR. FOR SPRAYING USE A MECHANICAL  
PREFILTER CONFINED AREAS  
USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR

Ventilation: GENERAL DILUTION  
AND LOCAL EXHAUST

Protective Gloves: IMPERMEABLE GLOVES

Eye Protection: SAFETY GLASSES

Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT

Work Hygienic Practices: WASH HANDS AND FACE THOROUGHLY BEFORE EATING OR  
DRINKING.

Supplemental Safety and Health

OVEREXPOSURE TO LEAD MAY RESULT IN SEVERE DAMAGE TO BLOOD  
FORMING, NERVOUS, URINARY, & REPROD. SYSTEMS. OVEREXPOSURE TO INSOLUBLE  
CHROMATES MAY CAUSE LUNG CANCER. OVEREXPOSURE TO TOLUENE MAY CAUSE  
LIVER DAMAGE. MISUSE CAN BE HARMFUL OR FATAL. PROLONGED/REPEATED  
EXPOSURE CAN CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====  
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 175-314F

Vapor Density: > AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 73

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid: EXCESSIVE HEAT AND SHOCK

RCES OF IGNITION

Hazardous Decomposition Products: BURNING, INCLUDING W/HEATED BY

WELDING/CUTTING, WILL PRODUCE SMOKE CARBON MONOXIDE/DIOXIDE

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/FEDERAL, STATE, & LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE ONLY IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE

DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.