

SEYMOUR OF SYCAMORE, INC. -- GREEN CP-3890-1000 AEROSOL -- 8010-00-958-8150

=====  
Product Identification  
=====

Product ID:GREEN CP-3890-1000 AEROSOL

MSDS Date:12/27/1989

FSC:8010

NIIN:00-958-8150

MSDS Number: BHMZS

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE, INC.

Address:917 CROSBY AVE.

City:SYCAMORE

State:IL

ZIP:60178

Country:US

Info Phone Num:815-895-9101

Emergency Phone Num:815

-895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 1.56%

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 15.18%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 6.24%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:N-HEPTANE  
CAS:142-82-5  
RTECS #:MI7700000  
Fraction by Wt: .77%  
OSHA PEL:500 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:HEXANE (N-HEXANE)  
CAS:110-54-3  
RTECS #:MN9275000  
Fraction by Wt: 25.93%  
OSHA PEL:500 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 20%  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE  
CAS:75-28-5  
Fraction by Wt: 13.3%  
OSHA PEL:ND  
ACGIH TLV:ND

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic

:EXPOSURE TO SOLVENT VAPORS

CONCENTRATION EXCEEDING THE ESTABLISHED THRESHOLD LIMIT VALUES CAN CAUSE RESPIRATORY SYSTEM IRRITATION.

Effects of Overexposure:EYE: IRRITATION ESPECIALLY UPON DIRECT CONTACT WITH THE SPRAY. SKIN: MAY CAUSE DEFATTING OF THE SKIN, LEADING TO IRRITATION AND DERMATITIS INHL: IRRITATION,HEADACHE,DIZZINESS,NAUS EA,POSS. UNCONSCIOUSNESS & ASPHYXIATIONINGST: IF INGESTED CALL A PHYICIAN IMMEDIATELY

=====  
===== First Aid Measures  
=====

First Aid:EYE: IMMED. FLUSH W/PLENTY OF WATER FOR 15 MINS., GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER INHL: REMOVE TO FRESH AIR, GIVE ARTIFICI AL RESPIRATION, GET IMMEDIATE MED. ATTN.INGST: CALL A PHYSICIAN IMMEDIATELY

=====  
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:NR

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE

INEFFECTIVE, WTR MAY BE

USED TO COOL CONTNRS TO PREVNT BURST-ING. IF WTR IS USED, FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES & SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOIDBREATHING VAPORS, VENTILATE AREA. WIPE UP WITH INERT MATERIALS AND PLACE IN APPROPRIATE CONTAINER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO HEAT OR PRO- LONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST. A SELF CONTAINED BREATHING APPARATUS

REQUIRED FOR  
CONCENTRATIONS ABOVE TLV LIMITS.

Ventilation:USE WITH ADEQUATE VETILATION, SUFFICIENT TO PREVETN INHALA-  
TION OF SOLVENT VAPORS.

Protective Gloves:OPTIONAL

Eye Protection:ONLY WHERE SPRAY MIST MIGHT GET INTO EYE

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:NA

Vapor Density:> AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85

===== Stability  
and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING MATERIALS

Stability Condition to Avoid:DO NOT STORE ABOVE 120F. KEEP FROM SPARKS,  
PILOT LIGHTS OR OPEN FLAME.

Hazardous Decomposition Products:MAY PROD HAZ FUMES W/HEATED TO DECOMP.  
FUMES MAY CONTAIN CARBON DIOXIDE/MONOXIDE. ALSO HYDROGEN CHLORIDE  
VAPOR.

===== Disposal Considerations =====

Waste Disposal Methods:DONOT INCINERATE AEROSOL. DISPOS  
E OF IN

ACCORDANCEWITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOTPLACE  
AEROSOL CANS IN HOME COMPACTOR. DO NOT PUNCTURE CAN.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek

competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.