View NSN Online: https://aerobasegroup.com/nsn/7930-00-985-6750

Product ID:KAR WAX MSDS Date:12/01/1985 FSC:7930 NIIN:00-985-6750 MSDS Number: BHMZZ === Responsible Party === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRING STREET City:BEDFORD State:MA ZIP:01730 Country:US Info Phone Num:1-617-5161 OR POISON CENTER Emergency Phone Num:1-617-5161 OR POISON CENT ER Preparer's Name: T. PITROLFFY CAGE:INDUS === Contractor Identification === Company Name: FEDERAL SPECIFICATIONS, PROMULGATED BY GSA Box:City:WASHINGTON State:DC Country:US CAGE:81348 Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRINGS RD City:BEDFORD State:MA ZIP:01730 Country:US Phone:1-617-667-5161 CAGE:INDUS

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 69% OSHA PEL:500 PPM ACGIH TLV:

100 PPM; 9293
======================================
 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:EYE IRRITATION, DRYING SKIN, MAY CAUSE HEADACHE, DIZZINESS, NAUSEA. Effects of Overexposure:EYE IRRITATION, DRYING SKIN, MAY CAUSE HEADACHE, DIZZINESS, NAUSEA.
======================================
First Aid:EYE CONTACT: FLUSH WITH WATER. SKIN CONTACT: WASH WITH MILD SOAP AND WAT ER, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR AND CALL PHYSICIAN.
======================================
Flash Point Method:TCC Flash Point:104 F/ 40.00 C Lower Limits:0.7 Upper Limits:6.9 Extinguishing Media:WATER SPRAY, CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:SCRAPE UP MATERIAL FROM SURFACE & COLLECT IN M ETALCONTAINER.
======================================
Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME. USE ADE-QUATE VENTILATION. AVOID PROLONGED CONTACT.
========= Exposure Controls/Personal Protection ===============
Respiratory Protection:SELF CONTAINED BREATHING APPARATUS ABOVE TLV LIMITS Ventilation:LOCAL EXHAUST Protective Gloves:RECOMMENDED Eye Protection:RECOMMENDED Other Protective Equipment:EYE BATH Supplemental Saf

ety and Health

Boiling Pt:B.P. Text:311 Vapor Pres:2 Vapor Density:4.7 Spec Gravity:0.78 Evaporation Rate & amp; Reference:0.12 (TOLENE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:WATER SPRAY, CO2, FOAM, DRY CHEMICAL Percent Volatiles by Volume:69

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME Hazar dous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS, DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.