

PLASTI-KOTE CO., INC. -- AERODOL SPRAY PAINT TT-E-489-G BLUE 15095 -- 8010-00-988-1458

=====
Product Identification
=====

Product ID:AERODOL SPRAY PAINT TT-E-489-G BLUE 15095

MSDS Date:01/08/1987

FSC:8010

NIIN:00-988-1458

MSDS Number: BHNBD

=== Responsible Party ===

Company Name:PLASTI-KOTE CO., INC.

Address:1000 LAKE ROAD

City:MEDINA

State:OH

ZIP:44256

Country:US

Info Phone Num:(216) 725-4511

Em

ergency Phone Num:(216) 725-4511

CAGE:HO182

=== Contractor Identification ===

Company Name:PLASTI-KOTE CO., INC.

CAGE:HO182

Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

Address:1000 LAKE ROAD

Box:City:MEDINA

State:OH

ZIP:44256

Country:US

Phone:330-725-4511

CAGE:07708

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalati

on: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO

Health Hazards Acute and Chronic: INHAL: NASAL & RESPIR IRRITATION, DIZZINESS, WEAK, FATIGUE, NAUSEA, HEADACHES, UNCONSCIOUSNESS, ASPHYXIATION. METHYLENE CHLORIDE-LOSS OF CONSCIOUSNESS & DEATH AS LOW AS 10,000 PPM NUMBNESS, RAPID HEART BEAT. EYES: SEVERE IRRITATION, RED, TEARS, BLURRED VISION, CONTACTS SHOULD NOT BE WORN. SKIN: PAINFUL IRRITATION. SWALLOW: GASTROINTESTINAL IRRITATION, NAUSEA, VOMIT & DIARRHEA.

Explanation of Carcinogenicity: METHYLENE CHLORIDE APPEARS ON ABOVE

AGENCIES LISTS OF SUSPECTED CARCINOGENS.

Effects of Overexposure: SEE ABOVE. PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. SEVERE OVEREXPOSURE IN LAB ANIMALS HAS ALSO CAUSED LIVER ABNORMALITIES AND DAMAGE TO KIDNEYS, LUNG & SPLEEN. INTENT MISUSE BY DELIBERATE CONCENTRATION & INHALE OF CONTENTS MAY BE HARMFUL OR FATAL. ALSO SKIN: IRRITATION, DEFATTING & DERMATITIS.

Medical Condition Aggravated by Exposure: CAN CAUSE ALLERGIC RESPIRATORY

REACTIONS AND/OR SKIN REACTIONS.

===== First Aid Measures =====

First Aid: INHALE: REMOVE TO FRESH AIR. IF BREATH IS DIFFICULT, ADMINISTER OXYGEN, IF STOPPED, GIVE CPR & SEEK MEDICAL HELP. EYES: FLUSH WITH WATER 15 MINS. WHILE LIFTING LIDS. GET MEDICAL ATTENTION IF SWALLOWED: DO NOT INDUCE VOMIT (ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMPNEUMONITIS, CAN BE FATAL) KEEP PERSON WARM/QUIET, GET MEDICAL ATTENTION/POISON CONTROL CENTER. SKIN: WASH WITH SOAP & WATER OR VARIOUS HAND CLEANERS. LAUNDRY CLOTHING

===== Fire Fighting Measures =====

Flash Point: NR

Lower Limits: 1.0

Extinguishing Media: ALCOHOL, FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE, USE TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITION/EXPLOSION. IF WATER USED FOG NOZZLE PREFERRED. SELF CONTAINING BREATH APPARATUS

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE &/OR AUTOIGNITE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE

HEAVIER THAN AIR, MAY TRAVEL
ALONG GROUND OR BY VENT & IGNITE AT LOCATIONS DISTANT

===== Accidental Release Measures =====

Spill Release Procedures:ELMINATE ALL IGNITION SOURCES. EVACUATE AND VENT AREA. TURN OFF HEATING/AIR CONDITIONING TO PREVENTVAPOR CONTAMINATION. ABSORB LIQUID ON PAPER OR VERMICULITE. FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL & TRANSFER TO CLOSED CONTAINER.

===== Handling and Storage =====
=====

Handling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120 F. IN DIRECT SUNLIGHT OR NEAR HEAT OR OPEN FLAMES. DO NOT PUNCTURE OR INCINERATE.

Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:TO AVOID BREATHING VAPORS OR SPRAY MIST, OPEN WINDOWS & DOORS OR USE OTHER MEANSTO ENSURE FRESH AIR ENTRY DURING APPLICATION & DRYING. WHERE VAPOR CONCENTRATIONIS GREATER THAN 100 PPM AN ORGANIC VAPOR TYPE RESPIRATOR IS ADVISED.

Ventilation:PROVIDE SUFFICIENT MECH (GENERAL) &/OR LOCAL EXHAUST VENT TOMAINTAIN EXPOSURE BELOW TLV'S. DO NOT USE IN CONFINED AREA.

Protective Gloves:CHEMICAL RESISTANT (NEOPRENE).

Eye Protection:CHEMICAL SPLASH GOGGLES (OSHA REGULATED)

Other Protective Equipment:SOLVENT RESISTANT BOOTS, APRON, HEADGEAR AND/OR FACESHIELDS SHOULD BE WORN WHERE SPLASHING IS POSSIBLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. AS WITH ALL CHEMICALS, MINIMIZE PERSONAL CONTACT AND/OR BREATHING OF VAPORS.

Supplemental Safety and Health
NK.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:104-300 F

Melt/Freeze Pt:M.P/F.P Text:1500 E

Vapor Density:> AIR

Spec Gravity:< 1

Evaporation Rate & Reference:>1, PROPELLANT