

DOW CORNING CORP -- DOW CORNING GN METAL ASSEMBLY SPRAY -- 9150-01-031-7238

=====
Product Identification
=====

Product ID:DOW CORNING GN METAL ASSEMBLY SPRAY

MSDS Date:07/13/1989

FSC:9150

NIIN:01-031-7238

MSDS Number: BHNJD

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergenc

y Phone Num:517-496-5900

Preparer's Name:JACK L.SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK RD.

Box:City:SOMERVILLE

State:NJ

ZIP:08876

Country:US
Phone:908-218-9000
CAGE:7B953

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 62.0%
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:PROPANE/BUTANE
CAS:68476-40-4
Fraction by Wt: 18.0%

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
Fraction by Wt
: 9.0%
OSHA PEL:10 MG/M3 TDUST (MO)
ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:WHITE MINERAL OIL
CAS:8042-47-5
RTECS #:PY8047000
Fraction by Wt: 6.0%

Ingred Name:GRAPHITE, NATURAL
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: 2.0%
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)
CAS:123-91-1
RTECS #:JG8225000
Fraction by Wt: 2.0%
OSHA PEL:S, 100 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:1,2

-BUTYLENE OXIDE (SARA III)

CAS:106-88-7

RTECS #:EK3675000

Fraction by Wt: 0.3%

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: MAY CAUSE EYE & SKIN

IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CENTRAL NERVOUS
SYSTEM DEPRESSANT. LOSS OF CONSCIOUSNESS AND EVEN DEATH CAN OCCU

R

AT HIGH LEVELS OF EXPOSURE.

Explanation of Carcinogenicity:1,4-DIOXANE AND 1,2-BUTYLENE OXIDE ARE
LISTED SUSPECTED CARNINOGEN BASED ON ANIMAL DATA.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR.
IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYE:

FL

USH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET
MEDICAL AT TENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH
SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING. GIVE
MILK OR USP MINERAL OIL. GET IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA
&

FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.CHLORINE AND SULFUR
COMPOUNDS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE UP WITH RAGS OR TOWELS.

LARGE SPILLS: WEAR NIOSH APPROVED RESPIRATOR. VENTILATE AREA. DIKE
TO RETAIN FLUI

D. PUMP UP FREE LIQUID. RESIDUE WILL EVAPORATE QUICKLY. DO NOT FLUSH TO SEWER OR WATERWAY.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120 F.DO NOT USE NEAR HEAT,OPEN FLAMES AND SPARKS.DO NOT PUNCTURE CAN.

Other Precautions:READ AND FOLLOW DIRECTIONS ON LABEL. DO NOT REUSE CONTAINERS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN HIGH VAPOR AREA, USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. USE SELF-CONTAINED BREATHING APPARATUS IF VAPOR LEVELS EXCEED 1000 PPM.

Ventilation:LOCAL EXHAUST RECOMMENDED TO CONTROL VAPORS BELOW 50% OF TLV.

Protective Gloves:NEOPRENE, PVA GLOVES RECOMMENDED.

Eye Protection:USE CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE. EYE WASH STATION & SAFETY SHOWER RECOMMENDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING, SMOKING OR USING TOILET FACILITIES. DO NOT BREATHE VAPORS OR MIST.

Supplemental Safety and Health
TARGET ORGANS ARE SKIN, CNS, CVS, AND EYES

=====
===== Physical/Chemical Properties =====

HCC:V3

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SOLVENT ODOR,PARTICULATE-CONTAINING SPRAY,BLACK
Percent Volatiles by Volume:85.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZIN

G AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CHLORINE COMPOUNDS,SULFUR OXIDES,METAL OXIDES,OXIDES OF CARBLON,TRACES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of De

fense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.