

CHEMRAY COATINGS, CORP. -- STAIN DARK OAK -- 8010-00-165-8628

=====  
Product Identification  
=====

Product ID:STAIN DARK OAK  
MSDS Date:10/27/1989  
FSC:8010  
NIIN:00-165-8628  
MSDS Number: BHQHG  
=== Responsible Party ===  
Company Name:CHEMRAY COATINGS, CORP.  
Address:209 N. MICHIGAN AVE.  
Box:NA  
City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Info Phone Num:201-245-1111 (8:30AM TO 4:30PM)  
Emergency Phone Nu  
m:800-924-9300 (CHEMTRAC 24 HOURS)  
Preparer's Name:FRED ARMSTRONG  
CAGE:OBRN9  
=== Contractor Identification ===  
Company Name:CHEMRAY COATING CORP  
Address:209 N MICHIGAN AVE  
Box:City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Phone:201-245-1111  
CAGE:33832  
Company Name:CHEMRAY COATINGS CORP.  
Address:209 N. MICHIGAN AVE.  
Box:NA  
City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Phone:800-924-9300  
CAGE:OBRN9

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 62%  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

Ingred Name:VOC. ORGANIC CMPD 4.60 LB/GAL LESS WATER & NPRS\* 552 G/L  
RTECS #:9999999VO

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:OVEREXPOSURE BY INHALATION CAN CAUSE  
NAUSEA, HEADACHE AND DIZZINESS.  
Effects of Overexposure:CAN CAUSE NAUSEA, HEADACHE, AND DIZZINESS FROM  
OVER INHALATION.  
Medical Cond Aggravated by Exposure:NONE

=====  
===== First Aid Measures =====  
=====

First Aid:EYE: FLUSH WITH WATER FOR 15 MINUTES OR UNTIL IRRITATION  
SUBSIDES. IF IRRITATION PERSISTS CALL A PHYSICIAN; SKIN: REMOVE  
CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER: INHAL:  
IF OVERCOME BY VAPORS REMOVE TO FRESH AIR, CALL A PHYSICIAN; INGEST:  
DO NOT INDUCE VOMITING CALL A PHYSICIAN.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:SCC  
Flash Point:103F/40C  
Autoignition Temp:Autoignition Temp Text:\*\*  
Lower Limits:0.9  
Upper Limits:7  
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL  
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR  
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPOR OR  
FUMES.  
Unusual Fire/Explosion Hazard:IF LEAK/SPILL HAS IGNITED USE WATER SPRAY  
TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====  
===== Accidental Release =====

se Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKAND OPEN FLAME. ADD ABSORBENT(SAND, DIRT, SAWDUST)TO SPILL. IF LARGE SPILL KEEP PRODUCT FROM ENTER- ING SEWERS AND WATERCOURSES BY DIKING, ADVISE AUTHORITIES IF PRODUCT ENTERED WATER SOURCES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRYWELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT AND EXTREME TEMPERATURES HOT OR COLD.

Other Precautions:AVOID EYE/SKIN CONTACT, INHALATION/INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA.

Ventilation:LOCAL EXHAUST-FACE VELOCITY 60FPM SPECIAL-USE ONLY W/ADEQUATE VENTILATION;MECHANICAL-USE EXPLOSION PROOF EQUIPMEN

T  
Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308F/155C

Melt/Freeze Pt:M.P/F.P Text:0F/-17.8C

Decomp Temp:Decomp Text:600F/316C

Vapor Pres: