View NSN Online: https://aerobasegroup.com/nsn/8030-00-463-7053

FIBER-RESIN CORPORATION -- FR-14 EPOXY RESIN SYSTEM -- 8030-00-463-7053

======== Product Identification ===========

Product ID:FR-14 EPOXY RESIN SYSTEM

MSDS Date:05/12/1989

FSC:8030

NIIN:00-463-7053

Kit Part:Y

MSDS Number: BHQKC === Responsible Party ===

Company Name: FIBER-RESIN CORPORATION

Address:170 W. PROVIDENCIA AVENUE

City:BURBANK

State:CA ZIP:91503 Country:US

Info Phone Num:1-800-624-9487

Emergency

Phone Num:1-800-624-9487 Preparer's Name:SAM ENGEL

CAGE:DO271

=== Contractor Identification === Company Name:3H B FULLER CO

Box:City:BURBANK

State:CA ZIP:91503 Country:US

Phone:800-624-9487;612-481-3300

CAGE:0HB93

Company Name: FIBER-RESIN CORP. Address: 170 W PROVIDENCIA AVE

Box:91503 City:BURBANK Phone:800-424-9300

CAGE:DO271

====== Composition/Information on Ingredients ========

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER RESIN

CAS:25068-38-6 RTECS #:KC2100000 Fraction by Wt: > 10 Ingred Name:1,4-BUTANEDIOLDIGLYCIDYL ETHER CAS:2425-79-8 Fraction by Wt: > 10% Ingred Name: PHENOL/FORMALDEHYDE/EPICHLOROHYDRIN RESIN CAS:28064-14-4 Fraction by Wt: > 20% Ingred Name: SILICA, CRYSTALLINE - TRIPOLI CAS:1317-95-9 RTECS #: VV7336000 Fraction by Wt: > 35% OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.1 MG/M3 RDUST;9293 ========== Hazards Identification ================= Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO ANTICIPATED CHRO NIC EFFECTS. Explanation of Carcinogenicity: THIS PRODUCT DOES NOT CONTAIN REGULATED LEVELS OF NTP, IARC OR OSHA LISTED CARCINOGENS. Effects of Overexposure: EYES: DIRECT EYE CONTACT WITH THE PRODUCT MAY CAUSE IRRITATION. SKIN: SOLVENTS ARE POTENTIAL DERMAL SENSITIZERS. INHALATION: INHALATION IS NOT A NORMAL ROUTE OF EXPOSURE. First Aid:EYES: FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. ============ Fire Fighting Measures ========================= Flash Point Method:TCC Flash Point:490 F/ 254 C Extinguishing Media: USE WATER SPRAY, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

========= Accidental Release Measures ============

Sp

MATERIAL.RESIDUE MAY BE REMOVED WITH A CHLORINATED SOLVENT.
======================================
Handling and Storage Precautions:STORE IN A COOL AND DRY LOCATION. Other Precautions:INCINERATE OR DISPOSE OF IN AN APPROVED INDUSTRIAL LANDFILL. FOR ADDITIONAL WASTE DISPOSAL ASSISTANCE CONTACT THE FIBER-RESIN CORPORATION. ALL COMPONENTS OFTHIS PRODUCT ARE REGISTERED UNDER REGULA TIONS O F THE TOXIC SUBSTANCE CONTROL ACT
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NORMALLY REQUIRED. Ventilation:STANDARD INDUSTRIAL VENTILATION. Protective Gloves:RUBBER GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:PREVENT CONTACT BY USING APPROPRIATE PROTECTIVE CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. Supplemental Safety and Health MSDS IS PREPARED TO COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD (29)
CFR 1910.1200). UNLISTED INGREDIENTS ARE NOT "HAZARDOUS" PER THIS OSHA STANDARD & ARE CONSIDERED A TRADE SECRETS OF THE FIBER-RES IN CORPORATION. IDENTITIES OF TRADESECRET INGREDIENTS (WHICH ARE ON THE TOSCA INVENTORY) WILL BE MADE AVAILABLE.
========= Physical/Chemical Properties ==========
pH:NE Viscosity:SYRUPY LIQUID Appearance and Odor:VISCOUS GREY LIQUID, ESSENTIALLY ODORLESS. ==================================
Stability Indicator/Materials to Avoid:YES AVOID CONTACT WITH STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD LOW MOLECULAR WEIGHT HYDRO- CARBONS, AS WELL AS CARBON MONOXIDE AND CARBON DIOXIDE. ===================================
Waste Disposal Methods:PRODUCT DOES NOT MEET THE DEFINITION OF HAZARDOUS WASTE UNDER THE U.S. EPA HAZARDOUS WASTE REGULA- TIONS 40 CFR 261. STATE OR LOCAL HAZARDOUS WASTE REGULATIONS MAY A

ill Release Procedures:WEAR RUBBER GLOVES & WIPE WITH ABSORBENT

PPLY

IF THEY ARE DIFFERENT FROM THE FEDERAL REGULATIONS. SEE BELOW.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsib ility for the suitability of this information to their particular situation.