

THE FLAMEMASTER CORPORATION -- CS 3300, PART A -- 8030-00-881-3933

===== Product Identification =====

Product ID:CS 3300, PART A

MSDS Date:07/25/1989

FSC:8030

NIIN:00-881-3933

Kit Part:Y

MSDS Number: BHQMY

=== Responsible Party ===

Company Name:THE FLAMEMASTER CORPORATION

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:1-818-982-1650

Emergency Phone Num:1-80

0-424-9300 CHEM TREC

Preparer's Name:SAMUEL L. ENGEL, SR.

CAGE:6N186

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

Company Name:THE FLAMEMASTER CORPORATION

CAGE:6N186

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENT

CAS:68611-50-7

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE ESTABLISHED. POSSIBLE SKIN
IRRITATION AFTER PROLONGED CONTACT, WITH RESULT-ING DERMATITIS. NOT
CONSIDERED TO BE A PRIMARY SKIN IRRITANT.
Effects of Overexposure:SKIN OR EYE IRRITATION.
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER, CONSULT PHYSICIAN.
SKIN: WASH WITH SOAP AND WATER. AND INGESTION: INDUCE VOMITING,
CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:> 200 F/ > 93 C
Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER.
Fire Fighting Procedures:NONE.
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND TRANSFER TO CONTAINER FOR
REACTION WITH CURING AGENT. CLEAN-UP RESIDUE WITH 1,1,1-
TRICHLOROETHANE THEN WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL AND DRY AREA, AWAY
FROM STRONG ACIDS.
Other Precautions:WASH HANDS BEFORE EATING, SMOKING OR DRINKING AFTER
HANDLING THIS PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED.
Ventilation:LOCAL EXH

AUST; AIR AND MECHANICAL (GENERAL); FAN.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.

Work Hygienic Practices:TRAIN EMPLOYEES IN SAFE HANDLING OF THIS PRODUCT.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:SEE BELOW

Vapor Pres:NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Spec Gravity:1.50 (H2O=1)

Evaporatio

n Rate & Reference:< 1 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE.

Appearance and Odor:RED PASTE, POLYSULFIDE ODOR. (MELTING POINT: LIQUID AT ROOM TEMP.)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS AND STRONG ACIDS.

Stability Condition to Avoid:OPEN FLAME.

Hazardous Decomposition Products:H2S, CO, CO2, SO2 AND SMOKE.

===== Disposal Considerations =====

=====

Waste Disposal Methods:REACT WITH CURING AGENT AND DISPOSE AS SOLID WASTE PER FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent

t professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.