View NSN Online: https://aerobasegroup.com/nsn/6830-01-296-2459

DU PONT E I DE NEMOURS AND CO INC -- FREON 116 REFRIGERANT/NITROUS OXIDE BLEND 90/10 -- 6830-01-296-2459

Product ID:FREON 116 REFRIGERANT/NITROUS OXIDE BLEND 90/10 MSDS Date:10/16/1996 FSC:6830 NIIN:01-296-2459 MSDS Number: BHQRM === Responsible Party === Company Name: DU PONT E I DE NEMOURS AND CO INC Address: DU PONT CHEMICALS FLUORCHEMICALS City:WILMINGTON Stat e:DE ZIP:19898 Country:US Info Phone Num:302-774-6822 Emergency Phone Num:800-441-3637,800-424-9300(CHEMTREC) Resp. Party Other MSDS Num.: 2051FR Preparer's Name:W.J. BROCK CAGE:2S827 === Contractor Identification === Company Name: ALLIED HEALTHCARE PRODUCTS, INC Box:UNKNOW CAGE:6V882 Company Name: DU PONT FLUOROPRODUCTS Address:1007 MARKET STREET Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:1-800-441-7515 Contract Num:SP0450-99-M-A244 CAGE:2S827 ======== Composition/Information o n Ingredients ========= Ingred Name: HEXAFLUOROETHANE ("FREON" 116) CAS:76-16-4 RTECS #:KI4110000 = Wt:90. Other REC Limits:NONE RECOMMENDED Ingred Name:NITROUS OXIDE CAS:10024-97-2 RTECS #:QX1350000 = Wt:10. Other REC Limits:50 PPM (DUPONT TWA) ACGIH TLV:50 PPM: 9394

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >15,000 MG (N2O)/KG. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IA RC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION OF HIGH CONCENTRATIONS OF VAPOR IS HARMFUL & MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS, OR DEATH. INTENTIONAL MISUSE OR DELIBERATE INHALATION MAY CAUSE DEATH WITHOUT WARNING. VAPOR RE DUCES OXYGEN AVAILABLE FOR BREATHING & IS HEAVIER THAN AIR. LIQUID CONTACT CAN CAUSE FROSTBITE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:CONTACT WITH THE LIQUID MAY CAUSE FROSTBITE. OVEREXPOSURE BY INHALATION

MAY INCLUDE NONSPECIFIC DISCOMFORT, SUCH

AS NAUSEA, HEADACHE, OR WEAKNESS; TEMPORARY NERVOUS SYSTEM DEPRESSION WITH ANESTHETIC E FFECTS SUCH AS DIZZINESS, HEADACHE, CONFUSION, INCOORDINATION, & LOSS OF CONSCIOUSNESS (LOSS OF VISION HAS BEEN OBSERVED ON REGAINING CONSCIOUSNESS WITH SEVERAL CASES OF PERMANENT VISUAL IMPAIRMENT AN D/OR BLINDNESS); IRRITATION OF THE UPPER RESPIRATORY PASSAGES; OR TEMPORARY ALTERATION OF THE HEART'S ELECTRICAL ACTIVITY WITH IRREGULAR PULSE

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE CENTRAL NERVOUS, CARDIOVASCULAR, REPRODUCTIVE, OR OCULAR SYSTEM MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

First Aid:INHALATION-IF INHALED, IMMEDIATE REMOVE TO FRESH AIR. KEEP PERSON CALM. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. SKIN-FLUSH

SKIN WITH PL ENTY OF WATER FOR 15 MIN. TREAT FOR FROST BITE BY GENTLY WARMING AREA. CALL A PHYSICIAN OF IRRITATION PERSISTS. EYE-IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MIN. CALL A PHYSICIAN. INGESTION- INGESTION IS NOT CONSIDERED A POTENTIAL ROUTE OF EXPOSURE.

Flash Point Method:TOC Flash Point:NONE Autoignition Temp:=600.C, 1112.F Extinguishing Media:AS APPROPRIATE FOR COMBUSTIBLES IN AREA.

Fire Fighting Procedures:USE WATER SPRAY OR FOG TO COOL CONTAINERS. SELF-CONTAINED BREATHING APPARATUS (SCBA) IS REQUIRED IF CYLINDERS RUPTURE OR RELEASE UNDER FIRE CONDITIONS.

Unusual Fire/Explosion Hazard:CYLINDERS EQUIPPED WITH PRESURE AND TEMPERATURE RELIEF DEVICES, BUT STILL MAY RUPTURE UNDER FIRE CONDITIONS. NITROUS OXIDE SUPPORTS COMBUSTION.

Spill Release Procedures: VENTILATE AREA, ESPECIALLY LO W OR ENCLOSED

PLACES WHERE HEAVY VAPORS MIGHT COLLECT. REMOVE OPEN FLAMES. USE SELF-CONTAINED BREATHING APPARATUS (SCBA) IF A LARGE SPILL OR LEAK OCCURS. USE APPROPRIATE P ERSONAL PROTECTIVE EQUIPMENT DURING CLEAN-UP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: AVOID BREATHING VAPORS AND CONTACT OF SKIN WITH LIQUID OR COLD VAPORS. USE WITH SUFFICIENT VENTILATION TO

KEEP EXPOSURE BELOW RECOMMENDED LIMITS. Other Precautions:STORE CONTAINERS IN A CLEAN, DRY AREA. DO NOT HEAT ABOVE 125F (52C).

Respiratory Protection: UNDER NORMAL MANUFACTURING CONDITIONS, NO RESPIRATORY PROTECTION IS REQUIRED WHEN USING THIS PRODUCT. SELF-CONTAINED BREATHING APPARATUS (SCBA) IS REQUIRED IF A LARGE RELEASE OCCURS.

Ventilation:NORMAL VENTILATION GENERALLY ADEQUATE.USE LOCAL EXHAUST WHEN LA

RGE AMOUNTS RELEASED, MECHANICAL IN LOW OR ENCLOSED PLACES

Protective Gloves: IMPERVIOUS GLOVES FOR HANDLING LIQUID.

Eye Protection: SPLASH GOGGLES FOR HANDLING LIQUID.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

INHALATION OF HIGH CONCENTRATIONS OF VAPOR IS HARMFUL AND MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS, OR DEATH. INTENTIONAL MISUSE OR DELIBERA

TE INHALATION MAY CAUSE DEATH WITHOUT WARNING. VAPOR REDUCES OXYGEN AVAILABLE FOR BREATHING AND IS HEAVIER THAN AIR. LIQUID CONTACT CAN CAUSE FROSTBITE.

HCC:G3 Boiling Pt:=-97.6C, -143.9F Vapor Pres:836 PSIA Vapor Density:3.9(AIR=1) Spec Gravity:1.587 Appearance and Odor:CLEAR, COLORLESS GAS. SLIGHT ETHEREAL ODOR. Percent Volatiles by Volume:100

St

ability Indicator/Materials to Avoid:YES

ALKÁLI OR ALKALINE EARTH METALS-POWDERED AL, ZN, BE, ETC. NITROUS OXIDE FORMS EXPLOSIVE MIXTURES WITH NH3, CO, H2, PH3.

Stability Condition to Avoid:AVOID OPEN FLAMES AND HIGH TEMPERATURES. Hazardous Decomposition Products:HYDROCHLORIC AND HYDROFLUORIC ACID,

POSSIBLY CARBONYL FLUORIDE, AND OTHER OXIDES OF NITROGEN. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Toxicological

Information:ANIMAL DATA: INHALATION 4-HOUR LC50: >800,000 PPM IN RATS. EFFECTS OBSERVED IN ANIMAL FROM EXPOSURES BY INHALATION INCLUDES DECREASED GROWTH RATE, PULMONARY CHANGES, IRREGULAR RESPIRATION, INCREASED U RINE VOLUME AND CREATILINE, REVERSIBLEPATHOLOGICAL CHANGES IN THE KIDNEYS, AND INCREASED URINARY FLUORIDE CONCENTRATION. ONE STUDY SHOWED NO CARDIAC EFFECTS IN DOGS AT A CONCENTRATION OF 20% "FREON" 116, WHILE ANOTHER STUDY DID SHOW SOME EFFECTS IN BOTH GUI NEA PIGS AND DOGS.

Waste Disposal Methods:RECLAIM BY DISTILLATION OR REMOVE TO A PERMITTED WASTE DISPOSAL FACILITY. COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Transport Information:DOT/IMO/IATA PROPER SHIPPING NAME: COMPRESSED GASES, N.O.S. (HEXAFLUOROETHANE, NITROUS OXIDE). HAZARD CLASS: 2.2. UN NO.: 1956. DOT/IMO LABEL: NONFLAMMABLE

GAS. SHIPPING CONTAINERS: CYLINDERS.

SARA Title III Information:TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312. ACUTE: YES,. CHRONIC: NO. FIRE: NO. REACTIVITY: NO. PRESSURE: YES. LISTS; EXTREMELY HAZARDOUS SUBSTANCE, CERCLA HAZARDOUS SUBSTANCE, TOXIC CHEMICALS -NO. Federal Regulatory Information:TSCA INVENTORY STATUS: REPORTED/INCLUDED.

Disclaimer (provided with this information by the compiling age ncies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.