

DYNALOY INC -- URESOLVE PLUS -- 6850-01-311-1180

===== Product Identification =====

Product ID: URESOLVE PLUS

MSDS Date: 09/01/1989

FSC: 6850

NIIN: 01-311-1180

MSDS Number: BHQRN

=== Responsible Party ===

Company Name: DYNALOY INC

Address: 7 GREAT MEADOW LN

City: EAST HANOVER

State: NJ

ZIP: 07936-1703

Country: US

Info Phone Num: 201-887-3678

Emergency Phone Num: 201-887-3678

Preparer's Name: JAY W. PARTON

CAG

E: 27905

=== Contractor Identification ===

Company Name: DYNALOY INC

Address: 7 GREAT MEADOW LN

City: EAST HANOVER

State: NJ

ZIP: 07936-1703

Country: US

Phone: 201-887-9270/201-887-3678 FAX

CAGE: 27905

Company Name: DYNALOY, INC.

Address: 1910 SOUTH STATE AVE.

Box: City: INDIANAPOLIS

State: IN

ZIP: 46203

Country: US

Phone: 317-788-9925; 703-527-3887

CAGE: 27908

===== Composition/Information on Ingredients =====

Ingred Name: 2-METHOXYETHANOL (EGME) (SARA III)

CAS: 109-86-4

RTECS #: KL5775000

Fract

ion by Wt: 60-80%
OSHA PEL:S, 25 PPM
ACGIH TLV:S, 5 PPM; 9192

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 2-4%
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:OTHER COMPONENTS (TYPE NOT SPECIFIED)

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2460 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MODERATELY TOXIC. EYE AND SKIN IRRITATION. HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, VOMITING, TREMOR, CONFUSION, KIDNEY DAMAGE. CHRONIC: REPEATED OVEREXPOSURE MAY CAUSE INJURY TO BONE MARROW AND BLOOD CELLS, KIDNEY, LIVER, AND TESTES.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:EYE, SKIN & RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, VOMITING, TREMOR, CONFUSION.
Medical Cond Aggravated by Exposure:BREATHING OF VAPOR AND/OR MIST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, OXYGEN MAY BE GIVEN BY QUALIFIED PERSONNEL. CALL A PHYSICIAN. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINU

TES, INCLUDING UNDER THE EYELIDS. CALL A PHYSICIAN. SKIN:REMOVE CONTAMINATED CLOTHING AND FLUSH WITH WATER. INGESTION: GIVE 2 GLASSES OF WATER AND INDUCE VOMITING IF THE PATIENT IS CONSCIOUS. CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:CC
Flash Point:117F,47C
Autoignition Temp:Autoignition Temp Text:545F
Lower Limits:1.8
Upper Limits:14.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. SMALL SPILLS SHOULD BE FLUSHED WITH LARGE QUANTITIES OF WATER. LARGE SPILLS SHOULD BE COLLECTED FOR DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT BREATHE VAPOR. USE WITH ADEQUATE VENTILATION. DO NOT GET IN EYES, ON SKIN, OR CLOTHING. ACCIDENTAL CONTACT SHOULD BE WASHED AWAY IMMEDIATELY.
Other Precautions:KEEP AWAY FROM HEAT AND FLAME. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES EYE IRRITATION. COMBUSTIBLE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED SUPPLIED AIR RESPIRATOR FOR HIGH CONCENTRATIONS.
Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION AND LOCAL EXHAUST REQUIRED. USE EXPLOSION PROOF MOTOR.
Protective Gloves:NEOPRENE
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. IMPERMEABLE APRON.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT

WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:256F,124C

Vapor Pres:6.2

Vapor Density:2.62

Spec Gravity:0.990

pH:12.8

Evaporation Rate & Reference:0.62(N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:BLUE TO GREEN BROWN LIQUID, SLIGHT PLEASANT
ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN A FURNACE WHERE PERMITTED UNDER
APPROPRIATE FEDERAL, STATE AND LOCAL REGULAT
IONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular

situation.