

PRODUCTS RESEARCH & CHEMICAL CORPORATION -- PRC P/N1426 PART B -- 8030-00-474-1419
===== Product Identification =====

Product ID:PRC P/N1426 PART B

MSDS Date:07/20/1988

FSC:8030

NIIN:00-474-1419

Kit Part:Y

MSDS Number: BHQTC

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Emergency

Phone Num:(714) 864-2310 AND (213) 240-2060

Preparer's Name:C.A. EISENHARD

CAGE:8K647

=== Contractor Identification ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:800-228-5635

CAGE:8K647

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300ST

EL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PHENOL-FORMALDEHYDE POLYMER
CAS:9003-35-4

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: LOCAL
IRRITATION, MAY CAUSE ALLERGIC SKIN RASH IN SENSITIZED INDIVIDUALS.
INHALATION: IRRITATION OF NOSE AND THROAT. INGESTION: MAY CAUSE
NAUSEA, VOMITTING, AND LIVER AND KIDNE Y DAMAGE.

Medical Con
d Aggravated by Exposure:PROLONGE DE EXPOSURE ABOVE PEL MAY
CAUSE HEADACHE, DIZZINESS AND UNCONCIOUSNESS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MIN. IF SYMPTOMS
PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF
SYMPTOMS PERSIST, CONSULT A PHYSICIAN.INHALATION: REMOVE TO FRESH
AIR, IF SYMP TOMS ARE PRESENT, CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

=====

Flash Point Method:SCC
Flash Point:85F / 29.44C
Lower Limits:1.8
Upper Limits:11% (MEK)
Extinguishing Media:CO2, DRY CHEMICAL, FOAM OR WATER SPRAY
Fire Fighting Procedures:USE AIR - SUPPLIED RESPIRATOR. USE WATER TO
COOL HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE
BUILDUP IN CLOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WEAR AIR-SUP

PLIED
RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBANT.
SCOOP INTO CONTAINERS. CLEAN WITH 1,1,1-TRICHLOROETHANE.

=====
Handling and Storage
=====

Handling and Storage Precautions:NA

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NA

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL. IN
CONFINED AREAS USE ORGANIC VAPOR CART RESP/AIR SUPPLIED RESPIRATOR.

Protective Gloves:SOLVENT R

ESISTANT GLOVES

Eye Protection:GOGGLES OR FULL FACE SHIELD

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Decomp Temp:Decomp Text:NA

Vapor Density:2.5 (MEK)

Spec Gravity:1.40

Evaporation Rate & Reference:3.8 (MEK)

Solubility in Water:SLIGHT

Corrosion Rate:NA

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE LISTED

H

azardous Decomposition Products:OXIDES OF CARBON, SO2, TRACES OF H2S

=====
Disposal Considerations
=====

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA
REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF
SPILLAGE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.