

PRATT AND LAMBERT INC -- ENAMEL ALKYD SG GREEN 24533 ID 745468 -- 8010-00-527-3197
===== Product Identification =====

Product ID:ENAMEL ALKYD SG GREEN 24533 ID 745468

MSDS Date:06/05/1989

FSC:8010

NIIN:00-527-3197

MSDS Number: BHQTN

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

E

mergency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

(VP 2 MM HG @ 20 DEG.C)

CAS:64475-85-0

RTECS #:PY8240000

OSHA PEL:500 PPM 2950 MG/CU.M

ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:SILI

CA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred
Name:LEAD CHROMATE
CAS:7758-97-6
RTECS #:GB2975000
OSHA PEL:.0500 MG/CU.M
ACGIH TLV:.0500 MG/CU.M

Ingred Name:VOC. ORGANIC CMPD 3.61 LB/GL LESS WATER & NPRS* 433 G/L
LESSWATER VOC 8.06 LB/GAL SOLIDS 967 G/L SOLIDS CALCULATED.
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING: CAN CAUSE GASTROINTES

TINAL

IRR/NAUSEA/VOMIT. ASPIRATION OF MAT'L MAY CAUSE CHEM PNEUMONITIS.
INHALATION: NOSE/THROAT IRRITA. HIGH CONCENTRATION MAY CAUSE
CENTRAL NERVOUS SYSTEM DEPRESSION CHAR BY
HEADACHES/DIZZINESS/NAUSEA/CONFUSION. EYE: MAY CAUSE EYE IRRITA.
SKIN: MAY CAUSE DEFATTING AND IRRITATION.

Explanation of Carcinogenicity:CHROMIUM/CERTAIN CHROMIUM

COMPOUNDS-NTP,IARC. CRYSTALLINE SILICA LIMITED EVIDENCE OF
CARCINOGENICITY IN HUMANS-IARC.

Effects of Overexposure:REPEATED EXPOSU

RE TO CRYSTALLINE SILICA MAY

CAUSE PNEUMOCONIOSIS. OCCUPATIONAL OVEREXPOSURE TO SOLVENTS ASSO
W/PERM BRAIN/NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
CONCENTRATING/INHALING CONT MA Y BE HARMFUL/FATAL. INSOLUBLE
CHROMATESMAY CAUSE LUNG CANCER. LEAD-BLOOD DAMAGE &
NERVOUS/URINARY/REPRODUCTIVE SYSTEMS.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY CONDITIONS

MAY BE AGGRA- VATED BY EXPOSURE TO CRYSTALLINE SILICA.

PREEXISTING KIDNEY CONDITIONS MAY B

E AGGRAVATED BY EXPOSURES TO

LEAD.

=====
===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING/GET MED ATTN. INHALATION:
REMOVE TO FRESH AIRIF BREATHING HAS STOPPED GIVE CPR. GET MED ATTN.
EYE: FLUSH W/WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS. GET MED
ATTN. SKIN: REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREA.
OBTAIN MED ATTN IF IRR'N PERSISTS. TREATMENT REQ FOR OVER-
EXPOSURE S/B DIRECTED AT THE CONTROL OF SY
MPTOMS AND THE CLINICAL
CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>102F 39C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
TO COOL CONT TO PREVENT POSSIBLE AUTO-IGNITION OR EXPLOSION. IF
WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT

/ELEC

EQUIP/SPARKS/FLAME. CONT MAY EXPLODE WHEN EXPOSED TO HEAT.
OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZ. OBTAIN MED
ATTN.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE/CONTAIN SPILL
WITHINERT MAT'L. TRANSFER LIQ'S/ABSORBENT DIKING MAT'L IN COVERED
METAL CONT'S FOR RECOVERY/DISPOSAL. USE ONLY NON-SPARKING TOOLS.
PREVENT CONTAM OF SEWERS/ STREAMS/GROUNDWATER W/SPILLED MAT'L/USED

ABSORBENT

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT BREATHE SANDING DUST OR REUSE EMPTY CONT. DO
NOT TAKE INTERN. CONT'ER S/BGROUNDED AND BONDED TO THE RECEIVING
CONTAINER. DO NOT WELD/BRAZE OR CUT CONT'R.NEVER USE PRESSURE TO
EMPTY. DRUM IS NOT A PRESSURE VESSEL. CLOSE AFTER EA USE.

===== Exposu
re Controls/Personal Protection =====

Respiratory Protection:WELL VENTILATED AREA-RESP NOT REQ. RESTRICTED
VENT-NIOSH CHEMICAL CARTRIDGE MAY BE REQ. IF SPRAYING, MECH
PREFILTER MAY BE REQ. IF TLV ARE EXCEEDED, USE A PROP FITTED
NIOSH/MSHA RESP W/APPROP PROTECTI ON FACTOR. SEE OSHA 29 CFR
1910.134.

Ventilation:PROVIDE DILUTION/LOCAL EXHAUST VENTILATION TO KEEP
CONCENTRAOF HAZARDOUS SUBSTANCES BELOW EXPOSURE LIMITS STATED.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH WITH SOAP AND WATER HANDS/FACE THOROUGHLY
BEFORE EATING OR DRINKING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:280F 388F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER.

Percent Volatiles by Volume:55

===== Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, INCLUD WHEN HEATED BY WELD/CUT WILL PRODUCE SMOKE/ CARBON MONOXIDE/CARBON DIOXIDE/OXIDES OF CHROMIUM & LEAD.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal

Methods: INCINERATE ONLY IN EPA PERMITTED FACILITY.

DISPOSE ONLY IAW FED/STATE/LOCAL REGS. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MAT'S. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or imp

lied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.