View NSN Online: https://aerobasegroup.com/nsn/9150-00-270-4057

HULS AMERICA INC. -- MIL-L-7808J, MSDS/PRODUCT NUMBER: 0425921 -- 9150-00-270-4057

Product ID:MIL-L-7808J, MSDS/PRODUCT NUMBER: 0425921 MSDS Date:01/16/1989 FSC:9150 NIIN:00-270-4057 **MSDS Number: BHRJZ** === Responsible Party === Company Name: HULS AMERICA INC. Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08854-0365 Country:US Info Phone Num:201-763-71 73 Emergency Phone Num:201-763-7173 Preparer's Name: P. A. PARKER MANAGER CAGE:0DH22 === Contractor Identification === Company Name: HUL AMERICA INC Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08854-0365 Country:US Phone:201-763-7173 CAGE:0DHB8 **Company Name: HULS AMERICA INC** Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08854-0365 Country:US Phone:908-981-5016 CAGE:0DH22

Ingred Name:NO HAZARD INGREDIENT

**IMMEDIATELY** 

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE AND SKIN IRRITATION, NAUSEA, VOMITING, RESPIRATORY TRACT IRRITATION. CHRONIC:NONE SPECIFIED BY MANUFACTURER. Explanation of Carcinogenicity:NONE OF THE CHEMICA LS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN. Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE. First Aid:INHALATION: REMOVE SUBJECT TO FRESH AIR. EYE: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INGES TION: DO NOT INDUCE VOMITING. GET IMMEDIA TE MEDICAL ATTENTION. Flash Point Method:COC Flash Point:400F,204C Extinguishing Media: USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. AVOID SPREADING LIQUID AND FIRE BY WATER FLOODING. Unusual Fire/Explosion Hazard: EXPOSURE TO HEAT BUILD S UP PRESSURE INCLOSED CONTAINERS, COOL WITH WATER SPRAY. Spill Release Procedures: COVER WITH AN INERT, ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: DO NOT USE OIL ABOVE THE MAXIMUM **RECOMMENDED OPERATING TEMPERATURE OF 400 F. WIPE UP SPILLS** 

Other Precautions: MAY SOFTEN SOME PLASTIC AND PAINT SURFACES. AVOID EYE AND SKIN CONTACT.

HCC:V6 Boiling Pt:B.P. Text:>450F,>232C Vapor Pres:1 Spec Gravity:< 1.0 Evaporation Rate & amp; Referen ce:SLOWER THAN BU/AC Solubility in Water:NEGLIGIBLE Appearance and Odor:STRAW CLEAR LIQUID; MILD ODOR. Percent Volatiles by Volume:NONE

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:TOXIC FUMES

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULA

TIONS. DO NOT CONTAMINATE

ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assu

me responsibility for the suitability of this information to their particular situation.