View NSN Online: https://aerobasegroup.com/nsn/8010-00-297-3819

CHEMRAY COATING CORP -- ENAMEL PHENOLIC OUTSIDE OLIVE DRAB 34088 -- 8010-00-297-3819

Product ID:ENAMEL PHENOLIC OUTSIDE OLIVE DRAB 34088

MSDS Date:04/02/1990

FSC:8010

NIIN:00-297-3819

MSDS Number: BHVSC === Responsible Party ===

Company Name: CHEMRAY COATING CORP

Address: 209 N MICHIGAN AVE

City:KENILWORTH

State:NJ ZIP:07033 Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name: FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name: CHEMRAY COATING CORP

Address: 209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ ZIP:07033 Country:US

Phone:201-245-1111

CAGE:33832

======= Composition/Information on Ingredients ========

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000 Fraction by Wt: 29% OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name: VOC=3.09 LBS/GAL OR 371 GRAMS/LIT



========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (> THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT MAY CAUSE HEADACHES A ND DIZZINESS, ARE ANESTHETIC, AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS.

Effects of Overexposur

e:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (> THAN APPROXIMATELY
1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT MAY
CAUSE HEADACHES A ND DIZZINESS, ARE ANESTHETIC, AND MAY HAVE OTHER
CENTRAL NERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure: NONE GENERALLY KNOWN.

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT; REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER. INHALATIO N: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

============ Fire Fighting Measures =========================

Flash Point Method:SCC Flash Point:103 F/40 C

Autoignition Temp: Autoignition Temp Text: 473 F

Lower Limits:0.9 Upper Limits:7

Extinguishing Media: CARBON DIOXIDE

, FOAM, WATER FOG, DRY CHEMICAL.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

======== Accidental Release Measures ==========

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWD

UST) TO SPILL. VENT AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM ENTERING SEWERS/WATERCO URSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER. ============= Handling and Storage ========================== Handling and Storage Precautions: STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT & EXTREME TEMPERATURES, HOT OR COLD. Other Precautions: AVOID EYE, SKIN CONTACT, INHALATION OR INGESTION OF MISTS, SPRAY O R VAPORS. AVOID BREATHING SANDING OR BLASTING DUST. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS. Ventilation: LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY W/ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT. Protective Gloves: CHEMICAL RESISTANT. Eye Protection: SPLASH GOGGLES OR FACE SHIELDS. Other Protective Equipment: USE CHEMICAL RESISTANT AP RON OR CLOTHING. Supplemental Safety and Health

======== Physical/Chemical Properties ===========

Boiling Pt:B.P. Text:308 F,155 C Melt/Freeze Pt:M.P/F.P Text:0 F(-17.8C) Decomp Temp:Decomp Text:600 F(316C) Vapor Pres: