

CHEMRAY COATING CORP -- PAINT, TRAFFIC, HIGHWAY-YELLOW 33538 -- 8010-00-900-3650
===== Product Identification =====

Product ID:PAINT, TRAFFIC, HIGHWAY-YELLOW 33538

MSDS Date:05/07/1990

FSC:8010

NIIN:00-900-3650

MSDS Number: BHVVW

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergenc

y Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:CHROME YELLOW (AS LEAD CHROMATE)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 7.5%

OSHA PEL:005 MG/M3

ACGIH TLV:005 MG/M3

Ingred Name:METHYL CHLOROFORM (1,1,1-T

RICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 13.4%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS:123-91-1

RTECS #:JG8225000

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 4%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:5

0 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 7%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 2.8%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC=2.07 LBS/GAL OR 248 GRAMS/LITER

RTECS #:9999999VO

===== Haza

=====
rds Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:EYES:IRRIT. SKIN:IRRIT, DRY, CRACKING.

MAY BE ABSORBED(TOXICITY ARE NOT ANTICIPATED BY THIS ROUTE ALONE UNDER NORMAL CONDITIONS OF USE). BREATHING HIGH CONCENTRATE OF VAPORS/MISTS MAY CAUSE IRRIT OF N OSE, THROAT, NERV SYS DEPRESS. ASTHMA LIKE CONDITION MAY BE AGGRAVATED. LUNG INFLAMMATION

/DAMAGE.SEE FILE FOR ADDIT INFO

Explanation of Carcinogenicity:CARCINOGEN, LEAD POISONING (MATERIAL SOLIDS CONTAIN LEAD CHROMATE).

Effects of Overexposure:EYES:IRRIT, DIRECT CONTACT-STING, TEARING, REDNESS. SKIN:IRRIT, REDNESS, BURNING, DRYING, CRACKING. IF PRE-EXISTING DISORDERS MAY BE MORE SUSCEPTIBLE. INHALE:HEADACHE, DROWSINESS, DIZZINESS, LOSS OF C OORDINATION, FATIGUE. INGESTION:NAUSEA,VOMIT, DIARRHEA, DROWSINESS, DIZZINESS. VOMITING CAN CAUSE LUNG INFLAMM/DAMAGE

Me

dical Cond Aggravated by Exposure:PRE-EXIST SKIN DISORDER MAY BE MORE SUSCEPTIBLE TO EFFECTS & PRE-EXISTING LUNG DISORDERS(E.G. ASTHMA-LIKE CONDITION)MAY BE AGGRAVATED.MAY BE ASSOCIATED W/CARDIAC ARRHYTHMIAS & AGGRAVATE LIVER DISORDER

=====
First Aid Measures =====

First Aid:EYES:GET FRESH AIR, FLUSH W/WTR. IF SYMP PERSIST, SEEK MED ATTN. SKIN:REMOVE CONTAM SHOES/CLOTHES, CLEANSE THORO W/SOAP & WTR. IF IRRI/RED DEVELOP/PERSIST, SEEK MED
. INHALE:MOVE TO FRESH AIR, SYMP PER SIST, SEEK MED IMMED. BREATH STOP GIVE CPR, IF BREATH DIFF, GIVE OXYGEN, SEEK MED IMMED. INGEST:DON'T INDUCE VOMIT/GIVE ANYTHING BY MOUTH. IF UNCONC/DROWSI PLACE ON LEFT SIDE W/HEAD DOWN. SEEK MED.

=====
Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:24 F/-4.4 C

Autoignition Temp:Autoignition Temp Text:960 F

Lower Limits:1.0

Upper Limits:11.0

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER F

OG, DRY CHEMICAL.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENT AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM ENTERING SEWERS/WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT & EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION OR INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY W/ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELDS.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:162F,72C

Melt/Freeze Pt:M.P/F.P Text:0 F(-17.8C)

Decomp Temp:Decomp Text:600 F(316C)

Vapor Pres:45-134@68F

Vapor Density:4.6 @ 77 F

Spec Gravity:1.68 (H2O=1)

Viscosity:70-80@77FKREB

Evaporation Rate & Reference:5.0 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SCHOOL BUS YELLOW WITH PAINT SOLVENT ODOR.

Percent Volatiles by Volume:40.8

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

CAN REACT W/OXIDIZING MATERIAL WHEN HEAT TO DECOMP. STRONG ACIDS/BASES, ALKALIES & REACTIVE METALS (IE SODIUM, POTASSIUM)

Stability Condition to Avoid: HIGH TEMPERATURE AND HIGH PRESSURE IN ALUMINUM SYSTEMS.

Hazardous Decomposition Products: CARBON MONOXIDE, PHOSGENE & HYDROCHLORIC ACID, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal

Methods: ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY. DISPOSE IN CONFORMITY WITH STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all lia-

bility for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.