View NSN Online: https://aerobasegroup.com/nsn/5970-01-217-8835

Product ID:CONATHANE CE-1164 MSDS Date:07/21/1989 FSC:5970 NIIN:01-217-8835 MSDS Number: BHWPS === Responsible Party === Company Name: CONAP INC. Address:1405 BUFFALO STREET City:OLEAN State:NY ZIP:14760 Country:US Info Phone Num:716-372-9650 Emergency Phone Num:716-372-9650 Preparer's Name: GEORGE C. KARPIN CAGE :16245 === Contractor Identification === Company Name: CONAP INC., WHOLLY OWNED SUBSIDIARY OF CYTEC INDUSTRIES INC. Address:1405 BUFFALO STREET Box:City:OLEAN State:NY ZIP:14760 Country:US Phone:716-372-9650 CAGE:16245 Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 10-20% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ing

red Name: PROPYLENE GLYCOL METHYL ETHER ACETATE CAS:108-65-6 RTECS #:AI8295000 Fraction by Wt: 20-30% Other REC Limits:100 PPM Ingred Name: TOLUENE-2,4-DIISOCYANATE (TDI) (SARA III) CAS:584-84-9 RTECS #:CZ6300000 Fraction by Wt: 25GM SOLID RESIN/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:LIQUID IS SEVERELY IRRITATING TO BODY TISSUES. TOLUENE DIISOCYANATE MAY SENSITIZE SEVERE ALLERGIC REACTIONS SUCH AS A CHEMICAL ASTHMA. PEL FOR TDI IS BELOW THE ODOR THRESHOLD. SOLVENTS ARE ABSORBED BY THE SKIN AND WITH CHRONIC OVEREXPOSUREMAY CAUSE PERMANENT CENTRAL NERVOUS SYSTEM DAMAGE KNOWN AS PAINTERS SYNDROME. Explanation of Carcinogenicity: TOLUENE DIISOCYANATE IS LISTED BY NTP AND IARC. SEE INDIVIDUAL REPORTS FOR DETAILS. Effects of Overexposure: EYE: SEVERE IRRITATION. SKIN: IRRITATION, DERMATITIS, SENSITIZED DERMATITIS. INHALED:RESPIRATORY IRRITATION, FLU-LI KE SYMPTOMS, ASTHMA, SENSITIZING, NARCOSIS, LOSS OF APPETITE. INGESTED:G/I IRRITATION, HEADACHE, NAUSEA, VOMITING, DIARRHEA. Medical Cond Aggravated by Exposure: SINCE TDI SENSITIZES DERMAL AND RESPIRATORY ALLERGYS, PEOPLE WITH ISOCYANATE SENSITIZATION, OR DERMATITIS, ASTHMA, AND OTHER SIMILAR DISORDERS SUCH AS EMPHYSEMA. ECZEMA, ETC. MAY BE AT INCREASED RISK.

First Aid:EYE:FLUSH W/WATER 15 MIN HOLD LIDS OPEN. SEE A DOCTOR.

SKIN:REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. GET MEDICAL CARE AS ASTHMATIC SYMPTOMS MAY DEVELOP EITHER IMMEDIATELY OR BE DELAYED SEVERAL HOURS. INGESTED:DO NOT INDUCE VOMITING. GIVE MILK OR WATER TO DRINK IF CONSCIOUS. GET IMMEDIATE MEDICAL CARE

Flash Point Method:TCC Flash Point:>45F,>7C Ext inguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND OR FLOOR, THEN 'FLASH BACK' FROM AN IGNITION SOURCE. FORMS HAZARDOUS DECOMPOSITION PRODUCTS IN A FIRE.

\_\_\_\_\_

Spill Release Procedures: ALWAYS USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. COVER SPILL WITH SAWDUST, VERMICULITE, ETC. ADD LIQUID DECONTAMINANT AND ALLOW TO SET FOR AT LEAST 10 MIN. COLLECT MATERIAL IN OPEN CONTAINERS AND ADD MORE DECONTAMINANT. Neutralizing Agent: WATER WITH 2-5% DETERGENT AND 0-10% AMMONIA. SEE SUPP DATA FOR ALTERNATE.

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A DRY AREA.

STORE BETWEEN 32-122F (50-81F, IDEAL). PROTECT FROM MOISTURE. PRODUCT WILL POLYMERIZE SLOWLY AT HIGHER TEMPERATURE Other Precautions:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. TREAT THEM WITH THE RESPECT DUE FULL ONES. DO NOT CUT,WELD,ETC. ON THEM.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR ANY TIME THE EXPOSURE IS ABOVE THE CEILING, SHORT TERM EXPOSURE LE

VEL, OR PEL, AND AT ALL TIMES DURING SPRAYING OPERATIONS. OTHER RESPIRATORS MAY BE USED F OR SHORT (1 HOUR) EXPOSURES ONLY!! Ventilation:GENERAL VENTILATION SUPPLEMENTED WITH LOCAL EXHAUST. AS

NEEDED TO MAINTAIN EXPOSURES BELOW PEL/TLV.

Protective Gloves: RUBBER, VINYL OR OTHER IMPERVIOUS

Eye Protection: GOGGLES OR FACE SHIELD \*\*NO CONTACTS!!\*

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWER. COVER AS MUCH SKIN AS POSSIBLE DURING OPERATIONS.

Work Hygienic Practices:USE STRICT

CHEMICAL HYGIENE PRACTICES. AVOID ALL CONTACT POSSIBLE. WASH THOROUGHLY AFTER USING. Supplemental Safety and Health
LD50 FOR TDI = 5800 MG/KG,LC50 FOR TDI = 4 HR @ 16-50 PPM. INHALATION AND SKIN CONTACT ARE MOST DAMAGING EXPOSURES. ALTERNATE DECONTAMINANT: 20% TERGITOL TMN-10 IN WATER. QPL46058-49 LISTS SEVERAL CONETHANE COMPOUNDS, CE-1164 IS INCLUDEDAS IS CE-1155 PART A. FOR MSDS OF THE LATTER SEE P/N IND A THIS NSN.
======================================
HCC:F2 Vapor Pres:3.7-8 MM Vapor Density:3.7 Spec Gravity:1.05 pH:UNKNON Solubility in Water:REACTS WITH WATER Appearance and Odor:CLEAR VISCOUS YELLOW LIQUID,NO ODOR Percent Volatiles by Volume:40
======================================
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS,WATER,AMINES,STRONG BASES,METAL COMPOUNDS,SURFACE ACTIVE MATERIALS. Stability Condition to Avoid:HIGH STORAGE TEMPERATURES, IGNITION SOURC ES Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
TRACES ON HYDROGEN CYANIDE, OXIDES OF NITROGEN, TOLUENE DIISOCYANATE.
======================================
Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, e xpressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.