

UNION CARBIDE CORPORATION -- WHITE ALKYD ENAMEL ID X-4609 -- 8010-00-298-2288

===== Product Identification =====

Product ID:WHITE ALKYD ENAMEL ID X-4609

MSDS Date:07/11/1988

FSC:8010

NIIN:00-298-2288

MSDS Number: BHWSS

=== Responsible Party ===

Company Name:UNION CARBIDE CORPORATION

Address:39 OLD RIDGEBURY ROAD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:ROUTINE INFO CONTACT L

OCAL SUPPLIER

Emergency Phone Num:1-800-822-4357 CANADA 514-640-6400

CAGE:36346

=== Contractor Identification ===

Company Name:HAMPTON ROADS SUPPLY UNION CARBIDE LINDE DIVISION

Address:3450 VIRGINIA BEACH BLVD

Box:12567

City:NORFOLK

State:VA

ZIP:23502-3123

Country:US

CAGE:7D711

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

===== Composition/Information on Ingredient

S =====

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 1 MM HG @ 20 C)  
CAS:64475-85-0  
RTECS #:PY8240000  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Haza

rds Acute and Chronic:ACUTE: LEAD INTOXICATION AND  
INHALATION CHRONIC:  
INGESTION

Explanation of Carcinogenicity:LISTED AS SUSPECTED CARCINOGENIC  
POTENTIAL TO MAN.

Effects of Overexposure:EYES: IRRITATION, REDNESS, TEARING, BLURRED  
VISION SKIN: IRRITATION, DERMATITIS  
INHALATION: NASAL  
AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, NAUSEA,HEADACHE,  
INGESTION: NAUSEA, VOMITING, DIARRHEA, ASPIR INTO LUNGS CAN CHEM  
PNEUM

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LARGE QTYS OF WTR, LIFTING UPPER/LOWER LIDS FOR  
15 MINUTES SKIN: THOROUGHLY WASH EXPOSED SKIN W/SOAP AND WATER.  
REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR  
IMMEDIATELY IF BREATHING HAS STOPPED GIVE CPR .INGESTION: DO NOT  
INDUCE VOMITING KEEP PERSON WARM, QUIET AND GET MEDICAL  
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Metho

d:TCC  
Flash Point:107F/41.67C  
Lower Limits:1.00

Extinguishing Media:CARBON DIOXIDE OR DRY CHEMICALS FOR SMALL FIRES,  
FOAM FOR LARGE FIRES

Fire Fighting Procedures:CLOSED CONTAINERS MAY BUILD EXPLOSIVE PRESSURE  
FROM HEAT, VAPORS ARE MORE THAN AIR AND MAY TRVL AT GROUND OR MAY  
MOVE BY VENT AND IGNITE BY PILOT LIGHTS OR

Unusual Fire/Explosion Hazard:OTHER FLAMES, SPARKS HEATERS, SMOKING,  
ELECTRIC MOTORS, STATIC DISCHARGE OR IGNITION SOURCES AT LOCATIONS  
DISTANT FROM MATERIAL  
HANDLING POINT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITION  
SOURCES DIKE AND CONTAIN SPILL W/INERT MATERIAL SUCH ASSAND OR  
EARTH. TRANSFER LIQS TO COVERED METAL CONTAINERS FOR RECOVERY OR  
DISPOSAL, OR REMOVE W ITH INERT ABSORBENT USE ONLY NON-SPARKING  
TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARAT  
AUS WHERE  
CONCENTRATIONS MAY BE ABOVE TLV LIMTS. BELOW TLV LIMITS, USE A  
NIOSH APPROVED VAPOR RESPIRATOR.

Ventilation:LOCAL EXHAUST

Protective Gloves:CHEMICAL GLOVES

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:EYE BATH AND SAFETY SHOWERS, TO PREVENT  
REPEATED OR PROLONG ED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND  
BOOTS.

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:  
323-390F

Vapor Density:>THAN AIR

Solubility in Water: