

MIDLAND DIVISION, THE DEXTER CORPORATION -- LAMINAR X500 LT STBLE HARDNER, PART B --  
8030-01-092-3879

=====  
===== Product Identification =====

Product ID:LAMINAR X500 LT STBLE HARDNER, PART B

MSDS Date:04/07/1988

FSC:8030

NIIN:01-092-3879

Kit Part:Y

MSDS Number: BHXFL

=== Responsible Party ===

Company Name:MIDLAND DIVISION, THE DEXTER CORPORATION

Address:31500 HAYMAN

City:HAYWARD

State:CA

ZIP:94544

Cou

ntry:US

Info Phone Num:415-471-7171

Emergency Phone Num:415-796-4972

Preparer's Name:T. GARRETT

CAGE:91342

=== Contractor Identification ===

Company Name:DEXTER CORP THE PACKAGING PRODUCTS DIV

Address:1-7 E WATER ST

Box:City:WAUKEGAN

State:IL

ZIP:60085-5614

Country:US

Phone:847-623-4200

CAGE:91342

=====  
===== Composition/Information on Ingredients =====

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)

CAS:822-06-0

RTECS #:MO1740000

Fraction by Wt: < 10%

ACGIH TLV:0.

005 PPM; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:N-BUTYL ACETATE (SARA III)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 10-20%  
OSHA PEL:150 PPM/200 STEL  
ACGIH TLV:150 PPM/200STEL;9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 10-20%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TALC (CONTAINING NO ASBESTOS)  
CAS:14807-  
96-6  
RTECS #:WW2710000  
Fraction by Wt: 5-10%  
OSHA PEL:2 MG/M3 RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9192

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:OVEREXPOSURE BY INHALATION MAY CAUSE  
IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, DIZZINESS OR  
DROWSINESS.  
Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY  
TRACT, HEADACHE, DIZZINESS OR DROWSINESS. SKIN & EYES: IRRITANT TO  
THE EYES & SKIN, ALSO SKIN SENSITIVITY.  
Medical Cond Aggravated by Exposure:RESPIRATORY PROBLEMS.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. EYES: FLUSH IMMEDIATELY  
WITH LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN:  
REMOVE CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP AND WATER.  
INGESTION: DRINK WATER. IF NECESSARY, CONSULT A PH

YSICIAN FOR ANY  
OF THESE CONDITIONS.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:91.0 F/32.8 C  
Lower Limits:1.10  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER  
FOG.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. VENTILATE AREA AND REMOVE WITH INERT ABSORBENT  
AND NON-SPARKING TOOLS. DISPOSE OF IN  
ACCORDANCE WITH LOCAL, STATE  
AND FEDERAL REGULATIONS. BEFOR E ATTEMPTING TO CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS SHOULD BE GROUNDED WHEN  
POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF FEW INCHES. ENSURE  
DRUM IS COMPLETELY EMPTY BEFORE WELDING, ETC.  
Other Precautions:THE DRUM SHOULD BE INDUSTRIALLY CLEANED PRIOR TO  
RE-USE. DO NOT FLAME CUT, BRAZE OR WELD WITHOUT A NIOSH APPROVED  
RESPIRATOR  
OR APPROPRIATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF GENERAL DILUTION/LOCAL EXHAUST FAILS TO  
ADEQUATELY DILUTE THE TWA/PEL OF THE MATERIAL, THEN RESPIRATORY  
PROTECTION SHOULD BE USED AS FOLLOWS: DO NOT BREATHE VAPOR OR SPRAY  
MIST. WEAR APPROPRIATE FI TTED RESPIRATOR APPROVED BY NIOSH/OSHA.  
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENT TO KEEP  
TWA/LEL BELOW ACCEPTABLE LIMITS & TO REMOVE DECOMPOSIT  
ION PRODUCT  
Protective Gloves:CHEMICAL RESISTANT GLOVES.  
Eye Protection:CHEMICAL SPLASH GOGGLES/FACE SHIELDS.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:259 F/126 C  
Vapor Density:> THAN AIR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:FUMES MAY CONTAIN CARBON MONOXIDE &  
OXIDES OF NITROGEN. MAY PRODUCE HAZARDOUS FU

MES WHEN HEATED TO  
DECOMP AS IN WELDING.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND  
FEDERAL REGULATIONS. BEFORE ATTEMPTING TO CLEAN UP.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this informatio  
n to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.