

ILLINOIS BROZE PAINT -- FLAT BLK 37038 (TT-E-516) ID 2603 -- 8010-00-910-8154

===== Product Identification =====

Product ID:FLAT BLK 37038 (TT-E-516) ID 2603

MSDS Date:06/01/1984

FSC:8010

NIIN:00-910-8154

MSDS Number: BHXPL

=== Responsible Party ===

Company Name:ILLINOIS BROZE PAINT

Address:300 E. MAIN STREET

Box:NA

City:LAKE ZURICH

State:IL

ZIP:60047

Country:US

Info Phone Num:312-438-8201

Emerge

ncy Phone Num:312-359-6433

CAGE:JO997

=== Contractor Identification ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

Company Name:ILLINOIS BROZE PAINT

Address:300 E. MAIN STREET

Box:NA

City:LAKE ZURICH

State:IL

ZIP:60047

Country:US

Phone:312-438-8201 OR 312-359-6433

CAGE:JO997

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88

-3

RTECS #:XS5250000
Fraction by Wt: 18.5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 8.2%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 26.7%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1
000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 30.7%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIANT; 9192

Ingred Name:INERT RESINS AND PIGMENTS
Fraction by Wt: BALANCE

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:EYES: PRIMARY IRRITANT SKIN: PRIMARY IRRITANT
INHALATION: ANESTHETIC, IRRITATION OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYSTEM.

DEPRESSION W/HEADACHE, DIZZINESS, STAGGERING GAIT,
CONFUSION, UNCONSCIOUSNESS, COMA

=====
First Aid Measures
=====

First Aid: EYES: FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEE PHYSICIAN SKIN: WIPE OFF WITH TOWEL, REMOVE REMAINDER WITH MINERAL SPIRITS, TURPENTINE, OR LACQUER THINNER, WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.

=====
Fire Fighting Measures
=====

Flash Point:-

40F/-40C

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard: CAN WILL RUPTURE FROM INTERNAL PRESSURE AT ABOUT 190F AND DISCHARGE FLAMMABLE CONTENTS. WHEN HEATED TO DECOMPOSITION TOXIC FUMES ARE FORMED.

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS) AVOID BREATHING VAPORS, VENTILATE AREA. REMOVE WITH INERT ABSORBENT.

=====
Handling and Storage
=====

Handling and Storage Precautions: DO NOT STORE ABOVE 120F, STORE LARGE QUANTITIES IN BUILDINGS DESIGNED, PROTECTED FOR STORAGE OF NFPA CLASS 1A FLAMMABLE LIQUIDS.

Other Precautions: DO NOT SPRAY IN EYES, DO NOT PUNCTURE OR INCINERATE CANS. DO NOT STICK PIN OR ANY SHARP OBJECTS INTO OPENING ON TOP OF CAN. FINGER MUST NOT PROTRUDE OVER SPRAY BUTTON.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: FOR CASUAL USE NONE REQUIRED, PROVIDED VENTILATION IS AVAILABLE AS OUTLINED BELOW.

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION.

Protective Gloves: NONE

Eye Protection: NO SPECIAL PROTECTION REQUIRED

Other Protective Equipment: NONE

Work Hygienic Practices: WASH WITH SOAP AND WATER

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt: B.P. Text: 104-279F

Vapor Density: >AIR

Evap

oration Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 88.2

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NK

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CARBON MONOXIDE,
PHOSGENE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.