

PRATT AND LAMBERT INC -- LACQUER ACRYLIC GRAY 26440, ID794634 -- 8010-00-935-7060
===== Product Identification =====

Product ID:LACQUER ACRYLIC GRAY 26440, ID794634

MSDS Date:10/14/1988

FSC:8010

NIIN:00-935-7060

MSDS Number: BHXPQ

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Eme

rgency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SA

RA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3
RDUST9293

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:VOC. ORGANIC CMPD 4.8 LB/GAL LESS WATER & NPRS* 576 G/L
LESS WATER VOC. 14.6 LB/GAL SOLIDS 1752 G/L SOLIDS CALCU
RTECS #:9999999VO

Ingred Name:B

UTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000

Fraction by Wt: AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:67

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION

Hazardous Decomposition Products:BURNING, INCLUDING W/HEATED BY
WELDING/CUTTING, WILL PRODUCE SMOKE CARBON MONOXID

E/DIOXIDE

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL, STATE, & LOCAL
REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE ONLY
IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE
DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is

formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.