

PRATT & LAMBERT, INC. -- LACQUER ACRYLIC MARRON 10049, ID794006 -- 8010-00-935-7061
===== Product Identification =====

Product ID:LACQUER ACRYLIC MARRON 10049, ID794006

MSDS Date:10/14/1988

FSC:8010

NIIN:00-935-7061

MSDS Number: BHXPB

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316

-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

(VAPOR PRESSURE 2 MMHG @ 20C)

CAS:64475-85-0

RTECS #:PY8240000

OSHA PEL:500 PPM 2950 MG/CU.M

ACGIH

TLV:100 PPM 525 MG/CU.M.

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;

9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VOC. ORGANIC CMPD 4.9 LB/GAL LESS WATER & NPRS* 588 G/L
LESS WATER VOC. 15.1 LB/GAL SOLIDS 1812 G/L SOLIDS CALCU

RTECS #:9999999VO

Ingred Name:VOC 4.84 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 581 G/L LESS WATER CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC

14.80 LB/GAL SOLIDS 1776 G/L SOLIDS CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LIQUID MATL MAY BE ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS. TOLUENE MAY CAUSE LIVER DAMAGE. ASPIRATION OF MATL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

HI CONCENTN MAY CAUS E ACUTE CENTRAL NERVOUS SYSTEM DEPRESS.OVEREXPSR TO SOLVENT W/PERMNT BRAIN & NERVS DAMAGE. MISUSE CAN BE HARMFUL/FATAL.

Effects of Overexposure:EYE: MAY CAUSE IRRITATION; SKIN: MAY CAUSE IRRITATION AND DEFATTING OF SKIN INHAL: NOSE/THROAT IRRIT., HEADACHES, DIZZINESS, NAUSEA, AND CONFUSION INGST: GASTROINTESTINAL IRRITATION, NAUS EA, AND VOMITING.

=====
===== First Aid Measures =====
=====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR FOR 15 MINS, LIFTING EYELIDS, GET MEDICAL ATTENTIONSKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE CONTAMINATED CLTHS,GET MEDICAL ATTNINHAL: REMOVE TO FRESH AIR IMMEDIATELY,G IVE ARTIFICIAL RESPIRATION,KEEP WARM ANDQUIET,GET MEDICAL ATTENTION IMMEDIATELY
INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN OR HOSPITAL IMMEDIATELY

=====
===== Fire Fighting Measures =====
=====

Flash Point:24F/-4.44C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFER-RED FOR LARGE FIRES.

Fire Fighting Procedures:SHOULD WEAR SCBA. WATER MAY BE INEFFECTIVE, BUT MAYBE USED TO COOL EXPSD CONTNRSTO PREVENT PRESS. BUILDUP W/EXPSD TO EXTRM HEAT. FOG NOZZLES ARE PREFERRED W/WTR

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSTION PRODUCTS MAY CAUSE A HEALTH HAZARD. WARNING!! FLAMMABLE

=====
===== Accidental Release Measures =====
=====

Spill Release Proc

edures:ELIMINATE ALL SOURCES OF IGNITION. DIKE &
CONTAIN SPILL W/INERT MATL. USE ONLY NON SPARKING TOOLS. PLACE
ABSORBENT DIKING MATL IN COVERED METAL CONT-AINERS FOR DISPOSAL.
PREVENT CONTAMINATION OF SEW- ERS, STREAMS,& GROUNDWTR W/SPILLED
MATLOR ABSRBNT

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LG QTY
IN COMPLIANCEW/OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH USE.
NEVER USE

PRESSURE TO EMPTY CONTAINERS.

Other Precautions:DO NOT TAKE INTERNALLY. EMPTY CONTAINERS MUST NOT BE
WASHED & REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE
GROUNDED/BONDED TO THE RECEIVING CONTAINER. DO NOTWELD,BRAZE, OR
CUT ON EMPTY CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREAS USE A NIOSH APPROVED CHEMICAL
CARTRIDGE RESPIRATOR. FOR SPRAYING USE A MECHANICAL
PREFILTER CONFINED AREAS
USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR

Ventilation:GENERAL DILUTION AND LOCAL EXHAUST

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE LIKELY NEEDED

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175-232F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:67

=====
===== Stability and Reactivity Dat

a =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION

Hazardous Decomposition Products:BURNING, INCLUDING W/HEATED BY
WELDING/CUTTING, WILL PRODUCESMOKE CARBON MONOXIDE/DIOXIDE

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL,STATE, &

LOCAL

REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE ONLY IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.