

CAAP COMPANY, INC. -- CAAPCOAT POLYURETHANE THINNER -- 8010-00-459-1756

=====
Product Identification
=====

Product ID:CAAPCOAT POLYURETHANE THINNER

MSDS Date:12/24/1988

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: BHXSK

=== Responsible Party ===

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Info Phone Num:203-468-0055

Emergency Phone Num:203-877-0375

Preparer's Name:RONALD D. ARENA

CAGE:LO402

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Phone:203-468-0055

CAGE:LO402

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STE

L
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES; SKI
N

IRRITANT. INHALATION RESPIRATORY IRRITANT. CHRONIC:
REPEATED/PROLONGED EXPOSURE MAY CAUSE OF DEFATTING OF SKIN &
DERMATITUS& POSSIBLE SENSITIZATION. INHAL: OF HIGH CONCENTRATIONS
ABOVE TLV'S MAY CAUSE NEURAL IMPAIRMENT.

Effects of Overexposure:VAPOR EXPOSURE: BURNING EYES, HEADACHE,
DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, AND NAUSEA.
CONTACT: MAY

CAUSE IRRITATION OF SKIN, BURNING OF SKIN OR EYES.

Medical Cond Aggravated by Exposure:PREEXISTING ALL
ERGIES, ASTHMA, EYE
& SKIN DISORDERMAY BE AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH MUCH WATER & CALL PHYSICIAN.
SKIN: WASH WITH SOAP AND WATER, REMOVE
CONTAMINATED CLOTHING. INHAL: REMOVE TO FRESH
AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY & CALL A PHYSICIAN.

INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN

=====
===== Fire Fighting Measures =====

=====

Flash Point Method:TCC

Flash Point:27F/-2.22C

Lower Limits:1.0

Upper Limits:7.5

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:USUAL METHODS FOR FLAMMABLE LIQUIDS. NOT MISCIBLE WITH WATER, ALTHOUGH WATER MAYBE USED TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:KEEP IGNITION SOURCES AWAY. CONTAIN W/ABSORBANT MATERIAL. USE PROTECTIVE EQUIPMENT. CLEAN UP ABSORBANT AND CONTAIN SECURELY. SWEEP & WET MOP WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IGNITION SOURCES AWAY. KEEP CLOSED WHEN NOT IN USE. KEEP AREA CLEAN. STORE BELOW 100F. Other Precautions:AVOID CONTACT WITH SKIN, EYES, AND CLOTHING. IF SPRAYING, DO NOT BREATHE MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR CARTRIDGE MASK OR S.C.B.A. FOR EMERGENCIES

Ventilation:LOCAL EXHAUST PREFERRED; MECHANICAL ACCEPTABLE SPECIAL SPRAY BOOTH IS RECOMMENDED FOR SPRAY

Protective Gloves:NEOPRENE OR POLYETHYLENE

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:RUBBER OR POLYETHYLENE APRON. RUBBER BOOTS FOR SPILLS

Work Hygienic Practices:WASH W/SOAP & WATER AFTER HANDLING. CONTACT LENSES NOT RECOMMENDED FOR SOLVENTS SINCE EYE INJURY MAY RESULT.

Supplemental Safety and Health
KEY1

:F3. KIT CONSISTS OF EIGHT PARTS. PART ONE HAS PNI A, PART TWO HAS PNI B, PART THREE HAS PNI C ... THROUGH PNI H, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:238-291F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:15

Vapor Density:3.5

Spec Gravity:0.848

Evaporation Rate & Reference:0.96

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR LIQUID. PLEASANT AROMATIC ODOR

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:IGNITION SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100F

Hazardous Decomposition Products:UNDER FIRE CONDITIONS, OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION PREFERRED. RCRA HAZARDOUS IGNITABLE WASTE. DISPOSE OF ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.