

RALKEM INC. -- PLASTIC POLISH, LIQUID PP560 B -- 7930-00-935-3794

=====
Product Identification
=====

Product ID:PLASTIC POLISH, LIQUID PP560 B

MSDS Date:01/01/1987

FSC:7930

NIIN:00-935-3794

MSDS Number: BHXTL

=== Responsible Party ===

Company Name:RALKEM INC.

Address:36977 FOX GLEN

City:FARMINGTON HILLS

State:MI

ZIP:48331

Country:US

Info Phone Num:313-661-0260

Emergency Phone Num:313-661-0260

CAG

E:ODE78

=== Contractor Identification ===

Company Name:RALKEM INC.

Address:36977 FOX GLEN

City:FARMINGTON HILLS

State:MI

ZIP:48331

Country:US

Phone:313-661-0260

CAGE:ODE78

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:64742-47-8

Fraction by Wt: 8-12%

OSHA PEL:500 PPM/2950 MG/CU.M

ACGIH TLV:100 PPM/525 MG/CU.M.

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Effect

s of Overexposure:MIGHT CAUSE SLIGHT SKIN IRRITATION

=====
First Aid Measures
=====

First Aid:WASH AFFECTED AREAS WITH SOAP AND WATER

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:117F/47.78C

Extinguishing Media:WATER FOG, DRY CHEMICAL, CO2, FOAM

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Proc

edures:SOAK UP RAGS

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURES

Other Precautions:SHAKE BEFORE USE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT REQUIRED

Protective Gloves:NOT REQUIRED

Eye Protection:NOT REQUIRED

Other Protective Equipment:NOT REQUIRED

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

HCC:F

4

Boiling Pt:B.P. Text: