

PRATTVILLE BUILDERS INC -- PRIMER EPOXY CTG CORRINHIB LEAD & CHR FREE --
8010-01-193-0517

===== Product Identification =====

Product ID:PRIMER EPOXY CTG CORRINHIB LEAD & CHR FREE

MSDS Date:03/19/1990

FSC:8010

NIIN:01-193-0517

Kit Part:Y

MSDS Number: BHXVJ

=== Responsible Party ===

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Inf

o Phone Num:205-365-2396/2145/312-455-2662NIGHT

Emergency Phone Num:205-365-2396/2145/312-455-2662NIGHT

Preparer's Name:W.A. ELLISON, OPRTNS MGR

CAGE:0EAH4

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Phone:205-365-2396/2145/312-455-2662NIGHT

CAGE:0EAH4

===== Com

position/Information on Ingredients =====

Ingred Name:ALIPHATIC AMINE ADDUCT

CAS:31326-29-1

Fraction by Wt: 25%

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 15%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER

CAS:107-98-2

RTECS #:UB7700000

Fraction by Wt: 50%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 5%

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:2-METHOXY-1-PROPANOL

CAS:1589-47-5

Fraction by Wt: < 5%

Ingred Name:VOC 5.88 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 706 G/L LESS WATER CALCULATED

RTECS #:9999999VO

Ingred Name:VOC 21.04 LB/GAL SOLIDS 25

25 G/L SOLIDS CALCULATED
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TOLUENE MAY CAUSE LIVER DAMAGE.
REPEATED CONTACT MAY CAUSE DERMATITIS. REPEATED/PROLONGED
OVEREXPOSURE MAY CAUSE PERMANENT BRAIN & NERV SYST DAMAGE. MISUSE
BY CONCENTRATE & INHALING OF MATERIAL MAY BE HARMFUL/FATAL. CAN
CAUSE
GASTROINTEST IRRIT. ASPIRATION OF MATERIAL INTO LUNGS MAY
CAUSE CHEM PNEUMONITIS CAN BE FATAL.
Effects of Overexposure:SWALLOW:GASTROINTESTINAL IRRIT,NAUSEA,VOMIT.
INHALE:MAY CAUSE NOSE/THROAT IRRIT, RSPRTRY SENSITIZ, HIGH
CONCENTRATE:ACUTE CENTRAL NERV SYS DEPRESS,HEADACHES,DIZZI,NAUSEA &
CONFUSION. EYES:SEVERE IRRIT & CORNEAL DAM.SKIN:LIQ MAY ABSORB
THROUGH SKIN IN HARMFUL AMTS, MAY BE SKIN SENSITIZATION (ALLERGIC
REACT) SEVERE IRRIT
Medical Cond Aggravated by Exposure
:N/K. TOLUENE HAS BEEN FOUND TO
CAUSE KIDNEY, LUNG AND SPLEEN DAMAGE IN LABORATORY ANIMALS.

=====
===== First Aid Measures =====

First Aid:SWALLOW: DO NOT INDUCE VOMIT, GIVE 1 OR 2 GLASS OF WTR TO
DILUTE (NEVER GIVE ANYTHING BY MOUTH IF UNCONSC) GET MED ATTN
IMMED. INHALE: REMOVE TO FRESH AIR, IF BREATH HAS STOPPED, GIVE
CPR. KEEP WARM/Q UIET. GET MED ATTN. EYES: FLUSH W/LG AMTS WTR,
LIFTING LIDS FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: IMMED
FLUSH
CONTAM AREA W/LG AMTS WTR. REMOVE CONTAM CLOTHES AS WTR APPLIED.
CONSULT PHYSICIAN.*

=====
===== Fire Fighting Measures =====

Flash Point:40 F/4 C
Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNED FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT MAY USE TO COOL
EXPOSED CONTAINERS TO PREVENT PRESS BUILD-UP/AUTO-IGNITE/EXPLOSION
FROM EXTREME HEAT. FOG

NOZZLES PREFERABLE.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A DELAYED HEALTH HAZARDS. OBTAIN MEDICAL ATTENTION. WARNING! FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM ALL IGNITE SOURCES. DIKE & CONTAIN W/INERT MATERIAL(E.G. SAND,EARTH). TRANSFER LIQ TO COVERED METAL CONTAINER FOR RECOVERY/DISPOSAL OR REMOVE W/INERT ABSORB.

USE ONLY NON-SP ARK TOOLS, PLACE IN COVERED METAL CONTAINER. **

Neutralizing Agent:N/K.** PREVENT CONTAM OF SEWERS, STREAMS & WATER W/SPILLED MATERIAL OR ABSORBENT

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 90 DEG F. IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS HAZARDOUS WASTE BASED ON ITS IGNITABILITY CHARACTERISTICS.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER USE. KEEP AWAY

FROM CHILDREN. AVOID SKIN CONTACT. EMPTY CONTAINERS MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED/BONDED TO RECEIVING CONTAINER.DO NOT WELD, BRAZE***

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MAY NOT REQUIRE USE OF RSPRTR IN WELL VENTED AREA. IN RESTRICT VENTILATION AREA: MAY NEED NIOSH ORGANIC VAPOR RSPRTR. SPRAYING: MECH PREFILTER MAY BE REQUIRED. CONFINED AREA:NIOSH/MSHA AIR SUPPLIED RS PRTR. SEE FILE FOR MORE INFORMATION.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENT IN VOL/PATTERN TO MAINTAIN CONCENTRATE OF HAZARD SUBSTANCE BELOW LOWEST EXPOSURE****

Protective Gloves:SOLVENT IMPERMEABLE-PROLONG/REPEAT CONT

Eye Protection:WEAR SAFETY SPECTACLES/CHEMICAL GOGGLES

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Work Hygienic Practices:N/K. **** LIMITS. REMOVE DECOMPOSITION PRODUCTS WHEN WELDING, CUTTING OR BRAZING OBJECTS COATED WITH THIS PRODUCT.

Supplementa

I Safety and Health

KEY1:F3. *** OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. SEE FILE FOR ADDITIONAL INFORMATION ON THIS PRODUCT.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:231 TO 405F

Vapor Density:> THAN AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:72

===== Stability and Reactivity Data =====

Stability Indicator/Materials t

o Avoid:NO

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS. ACCELERATORS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:MAY OCCUR WITH ADDITION OF EXCESS HARDENER. KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

==

Waste Disposal Methods:DISPOSE ONLY IN ACCORD W/FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. CONTAMINATED ABSORBANT MAY BE DISPOSED IN HAZARD WASTE LANDFILL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.