

EXXON CO USA, A DIV OF EXXON CORP. -- TURBO OIL 2380;PRO.CODE:217556-02380 --
9150-00-913-9717

===== Product Identification =====

Product ID:TURBO OIL 2380;PRO.CODE:217556-02380
MSDS Date:06/01/1989
FSC:9150
NIIN:00-913-9717
MSDS Number: BHXYX
=== Responsible Party ===
Company Name:EXXON CO USA, A DIV OF EXXON CORP.
Address:800 BELL ST
Box:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US

Info

Phone Num:713-656-5949
Emergency Phone Num:713-656-3424/2443
CAGE:29700

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.
Box:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US
Phone:713-656-5949 / 713-656-3424
CAGE:29700

===== Composition/Information on Ingredients =====

Ingred Name:BASE LUBRICANT OF POLYOL ESTERS
Fraction by Wt: >99.0%
Other REC Limits:NONE SPECIFIED

Ingred Name:PROPRIETARY ADDITIVES
Fraction by Wt: BALANCE
Other REC Limits:NONE SPECIF

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 5G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN OR
RESPIRATORY TRACT;CNS EFFECTS LIKE HEADACHE,DIZZINESS,NAUSEA AND
VOMITING.CHRONIC:DRYING OF SKIN,DEFATTING OR DERMATITIS.
Explanation of Carcinogenicity:DATA PER MSDS
Effects of Overexposure:SEE HEA
LTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKI
N:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:475F,246C
Lower Limits:1.0
Upper Limits:12.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE
NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
MATERIAL IF POSSIBLE;USE SUITABLE INERT ABSORBENT MATERIAL AND
RECOVER FOR PROPER DISPOSAL IN

AN APPROVED CONTAINER.
Neutralizing Agent:NOT APPLICABLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NORMALLY NEEDED. USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic P

ractices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

=====
Physical/Chemical Properties
=====

HCC:V6

Boiling Pt:B.P. Text:752F,400C

Vapor Pres:5.0

Spec Gravity:0.98

pH:NEUTRL

Evaporation Rate & Reference: