

GARDINER SOLDER COMPANY DIV GARDINER METAL CO -- TIN LEAD ANTIMONY ALLOY,XM-200
CORE.C.#181 -- 3439-01-087-1536

=====
Product Identification
=====

Product ID:TIN LEAD ANTIMONY ALLOY,XM-200 CORE.C.#181

MSDS Date:05/01/1990

FSC:3439

NIIN:01-087-1536

MSDS Number: BHXZM

=== Responsible Party ===

Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO

Address:4820 S CAMPBELL AVE

City:CHICAGO

State:

IL

ZIP:60632-1494

Country:US

Info Phone Num:312-847-0100

Emergency Phone Num:312-847-0100

CAGE:84311

=== Contractor Identification ===

Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO

Address:4820 S CAMPBELL AVE

Box:City:CHICAGO

State:IL

ZIP:60632-1494

Country:US

Phone:312-847-0100 CHEMTREC AFTER HOURS

CAGE:84311

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 5-94.8%

Other REC Limits:

NONE SPECIFIED

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TIN

CAS:7440-31-5

RTECS #:XP7320000

Fraction by Wt: 5-94.8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

Ingred Name:ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000

Fraction by Wt: 0.2-2.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.5 MG/M3

0-09-7

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SHORT TERM EXPOSURE TO WELDING FUMES, GASES OR DUST MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES.METALLIC TASTE IN MOUTH .IRRITATION OF RESPIRATORY TRACT.

Explanatio

n of Carcinogenicity:LEAD IS REGULATED BY OSHA UNDER 1910.1025

Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. WATERY EYES, HEADACHE, BREA THING DIFFICULTY, FREQUENT COUGHING AND/OR CHEST PAINS MAY OCCURE FROM ACUTE EXPOSURE. TOXIC GASES CAN BE FATAL.

Medical Cond Aggravated by Exposure:SOME WORKERS MAY BE AFFECTED BY A P

RE-EXISTING CONDITION OR OTHER OCCUPATIONAL ILLNESS BECAUSE OF THE WIDE VARIATION IN INDIVIDUAL SUSCEPTIBILITIES.

=====
===== First Aid Measures =====

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF NO DETECTABLE PULSE, BE GIN EXTERNAL HEART MASSAGE.

EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:NOT FLAMMABLE;DO NOT USE WATER;USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fi

re/Explosion Hazard:NONE EXPECTED;FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE.

===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection:OSHA APPROVED GOGGLE
S/FACE SHIELD W/LENS

Other Protective Equipment:FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WASH AFTER USE .FOLLOW GOOD INDUSTRIAL HYGIENE PRACTICES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:2516F,1380C

Melt/Fre

eze Pt:M.P/F.P Text:361F,183C
Vapor Pres:1
Spec Gravity:7.55-11.0
Solubility in Water:INSOLUBLE
Appearance and Odor:SILVER GREY SOLID,ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH TEMPERATURES
Hazardous Decomposition Products:WELDING AND CUTTING OPERATION MAY
INCLUDE OXIDES OF THE METALS,METAL FUMES ABOVE 1832F

===== Disposal Considerations =
=====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify a
nd
assume responsibility for the suitability of this information to their
particular situation.